

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

FIXAGRES FLEX CAPA GRUESA



Version: 8

Revision date: 26/03/2020

Page 1 of 10

Print date: 26/03/2020

SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: FIXAGRES FLEX CAPA GRUESA
Product Code: FCGR

1.2 Relevant identified uses of the mixture and uses advised against.

Tile adhesive

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **FIXCER PRODUCTS, S.A.U.**
Address: CTRA. SANT CUGAT KM. 3
City: CERDANYOLA DEL VALLÈS
Province: BARCELONA
Telephone: 93 586 20 03
Fax: 93 586 10 91
E-mail: fixcer@fixcer.com
Web: www.fixcer.com

1.4 Emergency telephone number: +34 91 562 04 20 (Available 24 hours)

Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420.

Información en español (24h/365 días). Únicamente con la finalidad de proporcionar respuesta sanitaria en caso de urgencia.

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

- Eye Dam. 1 : Causes serious eye damage.
- STOT SE 3 : May cause respiratory irritation.
- Skin Irrit. 2 : Causes skin irritation.
- Skin Sens. 1 : May cause an allergic skin reaction.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Danger

H statements:

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.

P statements:

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

FIXAGRES FLEX CAPA GRUESA



Version: 8

Revision date: 26/03/2020

Page 2 of 10

Print date: 26/03/2020

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor/...
P321 Specific treatment (see ... on this label).
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container to suitable container.

Contains:
Cement, portland, chemicals

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
CAS No: 1317-65-3 EC No: 215-279-6	[1] Calcium Carbonate	50 - 75 %	-	-
CAS No: 65997-15-1 EC No: 266-043-4	[1] Cement, portland, chemicals	20 - 25 %	Eye Dam. 1, H318 - STOT SE 3, H335 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

FIXAGRES FLEX CAPA GRUESA



Version: 8
Revision date: 26/03/2020

Page 3 of 10
Print date: 26/03/2020

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Contact with eyes may cause irreversible damage.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

Request immediate medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

The product does not present any particular risk in case of fire.

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

FIXAGRES FLEX CAPA GRUESA



Version: 8

Revision date: 26/03/2020

Page 4 of 10

Print date: 26/03/2020

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

-

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
Calcium Carbonate	1317-65-3	United Kingdom [1]	Eight hours		10 (total inhalable) 4 (respirable)
			Short term		
		United States [2] (Cal/OSHA)	Eight hours		10 (Total dust) 5 (Respirable fraction)
			Short term		
		United States [3] (NIOSH)	Eight hours		10 (Total dust) 5 (Respirable fraction)
			Short term		
		United States [4] (OSHA)	Eight hours		15 (Total dust) 5 (Respirable fraction)
			Short term		
Cement, portland, chemicals	65997-15-1	España [5]	Eight hours		4 (fracción respirable)
			Short term		
		United Kingdom [1]	Eight hours		10 (inhalable dust) 4 (respirable dust)
			Short term		
		United States [2] (Cal/OSHA)	Eight hours		10 (Total dust) 5 (Respirable fraction)
			Short term		
		United States [3] (NIOSH)	Eight hours		10 (Total dust) 5 (Respirable fraction)
			Short term		

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

FIXAGRES FLEX CAPA GRUESA



Version: 8

Revision date: 26/03/2020

Page 5 of 10

Print date: 26/03/2020

		United States [4] (OSHA)	Eight hours	15 (Total dust) 5 (Respirable fraction) 50 (mppcf: Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques. Conversion factors - mppcf X 35.3 = million particles per cubic meter = particles per c.c.)
			Short term	

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[2] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[3] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[4] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).




[5] Según la lista de Valores Límite Ambientales de Exposición Profesional adoptados por el Instituto Nacional de Seguridad y Salud en el Trabajo (INSST) para el año 2018.

The product does NOT contain substances with Biological Limit Values.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	Cement-glue		
Breathing protection:			
PPE:	Particle filter mask		
Characteristics:	«CE» marking, category III. Made of filtering material, it covers nose, mouth and chin.		
CEN standards:	EN 149		
Maintenance:	Check for any tears, defects, etc. before use. Since it is disposable individual protection equipment, it should be replaced after use.		
Observations:	Does not protect worker unless properly adjusted. Follow the manufacturer's instructions regarding suitable use of the equipment.		
Filter Type needed:	P2		
Hand protection:			
PPE:	Protective gloves against chemicals.		
Characteristics:	«CE» marking, category III.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
Eye protection:			
PPE:	Protective goggles against particle impacts.		
Characteristics:	«CE» marking, category II. Eye protector against dust and smoke.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



FIXAGRES FLEX CAPA GRUESA

Version: 8

Revision date: 26/03/2020

Page 6 of 10

Print date: 26/03/2020

Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.
Skin protection:	
PPE:	Protective clothing.
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.
CEN standards:	EN 340
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.
PPE:	Work footwear.
Characteristics:	«CE» marking, category II.
CEN standards:	EN ISO 13287, EN 20347
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Odourless powder with characteristic colour

Colour: N.A./N.A.

Odour: N.A./N.A.

Odour threshold: N.A./N.A.

pH: N.A./N.A.

Melting point: N.A./N.A.

Boiling Point: N.A./N.A.

Flash point: N.A./N.A.

Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A.

Lower Explosive Limit: N.A./N.A.

Upper Explosive Limit: N.A./N.A.

Vapour pressure: N.A./N.A.

Vapour density: N.A./N.A.

Relative density: N.A./N.A.

Solubility: N.A./N.A.

Liposolubility: N.A./N.A.

Hydrosolubility: N.A./N.A.

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A.

Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A.

Oxidizing properties: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Dropping point: N.A./N.A.

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

FIXAGRES FLEX CAPA GRUESA



Version: 8
Revision date: 26/03/2020

Page 7 of 10
Print date: 26/03/2020

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Product classified:

Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

FIXAGRES FLEX CAPA GRUESA



Version: 8
Revision date: 26/03/2020

Page 8 of 10
Print date: 26/03/2020

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.
No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.
Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

14.1 UN number.

Transportation is not dangerous.

14.2 UN proper shipping name.

Description:

ADR: Transportation is not dangerous.

IMDG: Transportation is not dangerous.

ICAO/IATA: Transportation is not dangerous.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

FIXAGRES FLEX CAPA GRUESA



Version: 8

Revision date: 26/03/2020

Page 9 of 10

Print date: 26/03/2020

Transportation is not dangerous.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

VOC content (p/p): 0 %

VOC content: 0 g/l

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

Classification codes:

Eye Dam. 1 : Serious eye damage, Category 1
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3
Skin Irrit. 2 : Skin irritant, Category 2
Skin Sens. 1 : Skin sensitiser, Category 1
Skin Sens. 1B : Skin sensitiser, Category 1B

Changes regarding to the previous version:

- Change in the hazard classification (SECTION 2.1).
- Changes in the composition of the product (SECTION 3.2).
- Modifications in the handling and storage precautions (SECTION 7.1).
- Modifications in the handling and storage precautions (SECTION 7.2).
- Modifications of the personal protective equipment (SECTION 8.2).
- Modification of the classification ADR/IMDG/ICAO/IATA/RID (SECTION 14).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

FIXAGRES FLEX CAPA GRUESA



Version: 8

Revision date: 26/03/2020

Page 10 of 10

Print date: 26/03/2020

Abbreviations and acronyms used:

CEN: European Committee for Standardization.

PPE: Personal protection equipment.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.