DECLARATION OF PERFORMANCE

Nº 135/18

Manufacturer:

Fixcer Products, S.A. - Ctra. Sant Cugat, Km 3 - 08290 Cerdanyola del Vallès (Barcelona)
Telf. 93 580 20 00 ; Fax 93 580 15 51
Planta: Avda. Gaudí, 15 – Pol. Ind. Rubí Sur – 08191 Rubí (Barcelona)

Identification code:

Name:	**HIDROFACIL**
Product type:	**DMO2P**

Intended use:

Liquid waterproofing membrane in dispersion for use under ceramic tiles

System of evaluation and verification of the constancy of performance:		**4**
	Sealing	**3**
Harmonised standard:	**EN 14891:2017**	
Notified body:	**LGAI Technological Center, nº 0370**	

Declared performance:

Essential characteristics:	Performance	Technical specifications
Initial tensile adhesion strength	≥ 0,5 N/mm^2	EN 14891:2017
Sealing	No penetration	
Crack propagation resistance under normal conditions	≥ 0,75 mm	
Crack propagation resistance at low temperatures (-20ºC)	≥ 0,75 mm	
Durability of the initial tensile adhesion against thermal ageing / weathering	≥ 0,5 N/mm^2	
Durability of the initial tensile adhesion against the action of water / moisture	≥ 0,5 N/mm^2	
Durability of initial tensile adhesion against freeze-thaw cycles	≥ 0,5 N/mm^2	
Durability of initial tensile adhesion against immersion in lime water	≥ 0,5 N/mm^2	
Durability of initial tensile adhesion against chlorinated water action	≥ 0,5 N/mm^2	
Discharge of hazardous substances	View SDS	

The performance of the previously identified product is in accordance with the declared performance.

This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer indicated above.

Signed by and on behalf of the manufacturer by:

Inés Sánchez
Directora Técnica

Cerdanyola del Vallès: 06-04-2021