



DECLARATION OF PERFORMANCE

Nº 023/13

Manufacturer:

Fixcer Products, S.A. - Ctra. Sant Cugat, Km 3 - 08290 Cerdanyola del Vallès (Barcelona)
Telf. 93 580 20 00 ; Fax 93 580 15 51
Planta: Avda. Gaudí, 15 – Pol. Ind. Rubí Sur – 08191 Rubí (Barcelona)

Identification code:

Name:	HIDROFIX
Product type:	CMO1P

Intended use:

Cementitious waterproofing membrane of modified polymers used under ceramic tiles for walls, floors and swimming pools both indoors and outdoors.

System of evaluation and verification of the constancy of performance:

	4
Sealing	3

Harmonised standard:

EN 14891:2012

Notified body:

LGAI Technological Center, nº 0370

Declared performance:

Essential characteristics:	Performance	Technical specifications
Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2012
Sealing	No penetration	
Crack propagation resistance under normal conditions	$\geq 0,75 \text{ mm}$	
Crack propagation resistance at low temperatures (-5°C)	$\geq 0,75 \text{ mm}$	
Durability of the initial tensile adhesion against thermal ageing / weathering	$\geq 0,5 \text{ N/mm}^2$	
Durability of the initial tensile adhesion against the action of water / moisture	$\geq 0,5 \text{ N/mm}^2$	
Durability of initial tensile adhesion against freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$	
Durability of initial tensile adhesion against immersion in lime water	$\geq 0,5 \text{ N/mm}^2$	
Durability of initial tensile adhesion against chlorinated water action	$\geq 0,5 \text{ N/mm}^2$	
Discharge of hazardous substances	View SDS	
Migration of substances	Compliant	EN 14944-3

The performance of the previously identified product is in accordance with the declared performance.

This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer indicated above.

Signed by and on behalf of the manufacturer by:

Inés Sánchez
Directora Técnica

Cerdanyola del Vallès: 06-04-2021

