

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## 1010011-RESINA ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 12 (replaces version 11)

Revision date: 10/03/2026

Page 1 of 12

Print date: 10/03/2026

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: RESINA ELASTICER  
Product Code: 1010011

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against.

Not available.

#### 1.3 Details of the supplier of the safety data sheet.

Company: **FIXCER PRODUCTS, S.A.U.**  
Address: CTRA. SANT CUGAT KM. 3  
City: CERDANYOLA DEL VALLÈS  
Province: BARCELONA  
Telephone: 93 586 20 03  
Fax: 93 586 10 91  
E-mail: fixcer@fixcer.com  
Web: www.fixcer.com

**1.4 Emergency telephone number:** Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. (Available 24 hours)

### SECTION 2: HAZARDS IDENTIFICATION.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

#### 2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Aquatic Chronic 2 : Toxic to aquatic life with long lasting effects.

Eye Irrit. 2 : Causes serious eye irritation.

Repr. 1B : May damage fertility or the unborn child.

Skin Irrit. 2 : Causes skin irritation.

Skin Sens. 1 : May cause an allergic skin reaction.

#### 2.2 Label elements.

##### Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:



Signal Word:

**Danger**

Hazard statements:

H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H360F May damage fertility.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P201 Obtain special instructions before use.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P273 Avoid release to the environment.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## 1010011-RESINA ELASTICER

Version 1 Date of compilation: 5/07/2010

Version 12 (replaces version 11)

Revision date: 10/03/2026

Page 2 of 12

Print date: 10/03/2026

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P321 Specific treatment (see ... on this label).  
P501 Dispose of contents/container to ...

EUH statements:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Contains:

reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight  $\leq 700$ )

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

1,3-Diisocyanato methylbenzene, 1,6-diisocyanato hexane polymer olyisocyanate based on hexamethyylene diisocyanate  
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

### 2.3 Other hazards.

| Identifiers                                                      | Name                    | PBT,vPvB or endocrine disrupting properties substances (concentration $\geq 0,1\%$ ) |
|------------------------------------------------------------------|-------------------------|--------------------------------------------------------------------------------------|
| Index No: 601-053-00-8<br>CAS No: 84852-15-3<br>EC No: 284-325-5 | 4-nonylphenol, branched | Substance with endocrine disrupting properties.                                      |

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

### 3.1 Substances.

Not applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

| Identifiers                                                                                                | Name                                                                                                      | Concentrate | (*)Classification - Regulation (EC) No 1272/2008                                        |                                                                       |
|------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-------------|-----------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
|                                                                                                            |                                                                                                           |             | Classification                                                                          | Specifics concentration limits and Acute toxicity estimate            |
| Index No: 603-074-00-8<br>CAS No: 25068-38-6<br>EC No: 500-033-5<br>Registration No: 01-2119456619-26-XXXX | reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight $\leq 700$ ) | 25 - 75 %   | Aquatic Chronic 2, H411 - Eye Irrit. 2, H319 - Skin Irrit. 2, H315 - Skin Sens. 1, H317 | Eye Irrit. 2, H319: C $\geq 5$ %<br>Skin Irrit. 2, H315: C $\geq 5$ % |
| CAS No: 9003-36-5<br>EC No: 500-006-8<br>Registration No: 01-2119454392-40-XXXX                            | Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol                      | 10 - 25 %   | Aquatic Chronic 2, H411 - Eye Irrit. 2, H319 - Skin Irrit. 2, H315 - Skin Sens. 1, H317 | -                                                                     |
| Index No: 603-103-00-4<br>CAS No: 68609-97-2<br>EC No: 271-846-8<br>Registration No: 01-2119485289-22-XXXX | oxirane, mono[(C12-14-alkyloxy)methyl] derivs.                                                            | 10 - 25 %   | Repr. 1B, H360F - Skin Irrit. 2, H315 - Skin Sens. 1, H317                              | -                                                                     |

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## 1010011-RESINA ELASTICER

Version 1 Date of compilation: 5/07/2010

Version 12 (replaces version 11)

Revision date: 10/03/2026

Page 3 of 12

Print date: 10/03/2026

|                                                                                                            |                                                                                                                        |              |                                                                                                                |   |
|------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|--------------|----------------------------------------------------------------------------------------------------------------|---|
| CAS No: 63368-95-6                                                                                         | [1] 1,3-Diisocyanato methylbenzene, 1,6-diisocyanato hexane polymer olyisocyanate based on hexamethyylene diisocyanate | 1 - 10 %     | Skin Sens. 1, H317                                                                                             | - |
| Index No: 601-053-00-8<br>CAS No: 84852-15-3<br>EC No: 284-325-5<br>Registration No: 01-2119510715-45-XXXX | [5] [7] 4-nonylphenol, branched                                                                                        | 0.1 - 0.25 % | Acute Tox. 4 *, H302 - Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Repr. 2, H361fd - Skin Corr. 1B, H314 | - |

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

\* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a European Union exposure limit in the workplace (see section 8.1).

[5] Substance included in the list established under Article 59, paragraph 1, REACH (Candidate substance).

[7] Substance included in the list established under Article 59, paragraph 1, REACH (Substances identified as having endocrine disrupting properties).

### SECTION 4: FIRST AID MEASURES.

**IRRITANT MIXTURE.** Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

#### 4.1 Description of first aid measures.

Delayed effects may occur after the exposure to the product.

#### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

#### Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

#### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

#### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

Repeated or prolonged eye contact may cause stinging, tearing, redness, swelling, and blurred vision.

Long-term chronic exposure may result in injury to certain organs or tissues.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

### SECTION 5: FIREFIGHTING MEASURES.

The product is NOT classified as flammable, in case of fire the following measures should be taken:

#### 5.1 Extinguishing media.

##### Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## 1010011-RESINA ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 12 (replaces version 11)

Revision date: 10/03/2026

Page 4 of 12

Print date: 10/03/2026

### Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

### **5.2 Special hazards arising from the substance or mixture.**

#### Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

### **5.3 Advice for firefighters.**

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

## SECTION 6: ACCIDENTAL RELEASE MEASURES.

### **6.1 Personal precautions, protective equipment and emergency procedures.**

For exposure control and individual protection measures, see section 8.

### **6.2 Environmental precautions.**

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

### **6.3 Methods and material for containment and cleaning up.**

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

### **6.4 Reference to other sections.**

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

## SECTION 7: HANDLING AND STORAGE.

### **7.1 Precautions for safe handling.**

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

### **7.2 Conditions for safe storage, including any incompatibilities.**

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

| Code | Description                                                                        | Qualifying quantity (tonnes) for the application of |                         |
|------|------------------------------------------------------------------------------------|-----------------------------------------------------|-------------------------|
|      |                                                                                    | Lower-tier requirements                             | Upper-tier requirements |
| E2   | ENVIRONMENTAL HAZARDS - Hazardous to the Aquatic Environment in Category Chronic 2 | 200                                                 | 500                     |

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## 1010011-RESINA ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 12 (replaces version 11)

Revision date: 10/03/2026

Page 5 of 12

Print date: 10/03/2026

### 7.3 Specific end use(s).

Not available.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

### 8.1 Control parameters.

Work exposure limit for:

| Name                                                                                                              | CAS No.    | Country            | Limit value | ppm | mg/m <sup>3</sup>                                                    |
|-------------------------------------------------------------------------------------------------------------------|------------|--------------------|-------------|-----|----------------------------------------------------------------------|
| 1,3-Diisocyanato methylbenzene, 1,6-diisocyanato hexane polymer olyisocyanate based on hexamethylene diisocyanate | 63368-95-6 | European Union [1] | Eight hours |     | 0,06 (Calculated as NCO, skin dermal and respiratory sensitization)  |
|                                                                                                                   |            |                    | Short term  |     | 0,012 (Calculated as NCO, skin dermal and respiratory sensitization) |

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

| Name                                                                                                                                                | DNEL/DMEL         | Type                                  | Value                         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|---------------------------------------|-------------------------------|
| reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight $\leq 700$ )<br>CAS No: 25068-38-6<br>EC No: 500-033-5 | DNEL<br>(Workers) | Inhalation, Chronic, Systemic effects | 12,25<br>(mg/m <sup>3</sup> ) |
| oxirane, mono[(C12-14-alkyloxy)methyl] derivs.<br>CAS No: 68609-97-2<br>EC No: 271-846-8                                                            | DNEL<br>(Workers) | Inhalation, Chronic, Local effects    | 0,98<br>(mg/m <sup>3</sup> )  |
|                                                                                                                                                     | DNEL<br>(Workers) | Inhalation, Chronic, Systemic effects | 13,8<br>(mg/m <sup>3</sup> )  |
| 4-nonylphenol, branched<br>CAS No: 84852-15-3<br>EC No: 284-325-5                                                                                   | DNEL<br>(Workers) | Inhalation, Chronic, Systemic effects | 0,5<br>(mg/m <sup>3</sup> )   |

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

|                                                                                                      |                                                                                                                                                                                                                                                                                                        |
|------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Concentration:                                                                                       | 100 %                                                                                                                                                                                                                                                                                                  |
| Uses:                                                                                                |                                                                                                                                                                                                                                                                                                        |
| Breathing protection:                                                                                |                                                                                                                                                                                                                                                                                                        |
| If the recommended technical measures are observed, no individual protection equipment is necessary. |                                                                                                                                                                                                                                                                                                        |
| Hand protection:                                                                                     |                                                                                                                                                                                                                                                                                                        |
| PPE:                                                                                                 | Non-disposable protective gloves against chemicals.                                                                                                                                                                                                                                                    |
| Characteristics:                                                                                     | «CE» marking, category III. Check the list of chemicals for which the glove has been tested.                                                                                                                                                                                                           |
| CEN standards:                                                                                       | EN 374-1, EN 374-2, EN 374-3, EN 420                                                                                                                                                                                                                                                                   |
| Maintenance:                                                                                         | A schedule for the periodical replacement of gloves should be established in order to guarantee their replacement before pollutants permeate them. The use of contaminated gloves could be more dangerous than not using gloves, since the pollutant can gradually accumulate in the glove's material. |



-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## 1010011-RESINA ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 12 (replaces version 11)

Revision date: 10/03/2026

Page 6 of 12

Print date: 10/03/2026

|                         |                                                                                                                                                                                                                                                              |                           |       |                          |      |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|-------|--------------------------|------|
| Observations:           | They are to be replaced whenever tears, cracks or deformations are observed or when exterior dirt could reduce their strength.                                                                                                                               |                           |       |                          |      |
| Material:               | PVC (polyvinyl chloride)                                                                                                                                                                                                                                     | Breakthrough time (min.): | > 480 | Material thickness (mm): | 0,35 |
| <b>Eye protection:</b>  |                                                                                                                                                                                                                                                              |                           |       |                          |      |
| PPE:                    | Protective goggles with built-in frame.                                                                                                                                                                                                                      |                           |       |                          |      |
| Characteristics:        | «CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.                                                                                                                                             |                           |       |                          |      |
| CEN standards:          | EN 165, EN 166, EN 167, EN 168                                                                                                                                                                                                                               |                           |       |                          |      |
| Maintenance:            | Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.                                                                          |                           |       |                          |      |
| Observations:           | Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.                                                                                                                                     |                           |       |                          |      |
| <b>Skin protection:</b> |                                                                                                                                                                                                                                                              |                           |       |                          |      |
| PPE:                    | Protective clothing.                                                                                                                                                                                                                                         |                           |       |                          |      |
| Characteristics:        | «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.                                                                                                                               |                           |       |                          |      |
| CEN standards:          | EN 340                                                                                                                                                                                                                                                       |                           |       |                          |      |
| Maintenance:            | In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.                                                                                                                                      |                           |       |                          |      |
| Observations:           | The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. |                           |       |                          |      |





### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

#### 9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: Not applicable/Not available due to the nature/properties of the product

Odour: Not applicable/Not available due to the nature/properties of the product

Odour threshold: Not applicable

Melting point: Not applicable

Freezing point: Not applicable

Boiling point or initial boiling point and boiling range: Not applicable

Flammability: Not applicable

Lower explosion limit: Not applicable

Upper explosion limit: Not applicable

Flash point: Not applicable

Auto-ignition temperature: Not applicable

Decomposition temperature: Not applicable

pH: Not applicable (Substance/mixture is non-soluble (in water)).

Kinematic viscosity: Not applicable

Solubility: Not applicable

Hydrosolubility: Not applicable

Liposolubility: Not applicable

Partition coefficient n-octanol/water (log value): Not applicable

Vapour pressure: Not applicable

Absolute density: Not applicable

Relative density: Not applicable

Relative vapour density: Not applicable

Particle characteristics: Not applicable

#### 9.2 Other information

##### Other safety characteristics

Viscosity: Not applicable

Dropping point: Not applicable

Blink: Not applicable

% Solids: Not applicable

### SECTION 10: STABILITY AND REACTIVITY.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## 1010011-RESINA ELASTICER



Version 1      Date of compilation: 5/07/2010

Version 12 (replaces version 11)

Revision date: 10/03/2026

Page 7 of 12

Print date: 10/03/2026

### 10.1 Reactivity.

The product does not present hazards by their reactivity.

### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

### 10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

### 10.4 Conditions to avoid.

Avoid any improper handling.

### 10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

### 10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

## SECTION 11: TOXICOLOGICAL INFORMATION.

Based on the properties of the epoxy components, and keeping in mind the toxicological data on similar preparations, this preparation can sensitise and irritate the skin, eyes, and respiratory tract.

The low molecular weight epoxy components are irritants to the eyes, mucous membranes, and skin. Repeated contact with the skin can lead to its irritation or sensitisation, possibly with accentuated autosensitisation to other epoxies.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

### 11.1 Information on hazard classes as defined in Regulation (EC) N° 1272/2008.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Repeated or prolonged eye contact may cause stinging, tearing, redness, swelling, and blurred vision.

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitizer, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Product classified:

Reproductive toxicant, Category 1B: May damage fertility or the unborn child.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## 1010011-RESINA ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 12 (replaces version 11)

Revision date: 10/03/2026

Page 8 of 12

Print date: 10/03/2026

h) STOT-single exposure;  
Not conclusive data for classification.

i) STOT-repeated exposure;  
Not conclusive data for classification.

j) aspiration hazard;  
Not conclusive data for classification.

### 11.2 Information on other hazards.

#### Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

#### Other information

There is no information available on other adverse health effects.

## SECTION 12: ECOLOGICAL INFORMATION.

### 12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

### 12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

### 12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Endocrine disrupting properties.

Substances with endocrine disrupting properties can cause in living organisms: hormone imbalance, decrease in the quality and quantity of gametes, fertility problems, alteration of reproductive behaviors, deformation of sexual organs, embryonic abnormalities, changes in the sex ratio of a species and / or developmental delays.

### 12.7 Other adverse effects.

The product is not affected by the Regulation (EU) 2024/590 of the European Parliament and of the Council of 7 February 2024 on substances that deplete the ozone layer.

No information is available about other adverse effects for the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS.

### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

## SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



## 1010011-RESINA ELASTICER

Version 1 Date of compilation: 5/07/2010

Version 12 (replaces version 11)

Revision date: 10/03/2026

Page 9 of 12

Print date: 10/03/2026

Transport documentation: Consignment note and written instructions

**Sea:** Transport by ship: IMDG.

Transport documentation: Bill of lading

**Air:** Transport by plane: ICAO/IATA.

Transport document: Airway bill.

### 14.1 UN number or ID number.

UN No: UN3082

### 14.2 UN proper shipping name.

Description:

ADR/RID: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT  $\leq$  700) / FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL), 9, PG III, (-)

IMDG: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT  $\leq$  700) / FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL), 9, PG III, MARINE POLLUTANT

ICAO/IATA: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT  $\leq$  700) / FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL), 9, PG III

### 14.3 Transport hazard class(es).

Class(es): 9

### 14.4 Packing group.

Packing group: III

### 14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-F

### 14.6 Special precautions for user.

Labels: 9



Hazard number: 90

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Proceed in accordance with point 6.

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 30 kg B

### 14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

## SECTION 15: REGULATORY INFORMATION.

This information is shown on the current Safety Data Sheet for the Preparation.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## 1010011-RESINA ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 12 (replaces version 11)

Revision date: 10/03/2026

Page 10 of 12

Print date: 10/03/2026

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Volatile organic compound (VOC)

VOC content (p/p): 0 %

VOC content: 0 g/l

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

Substances including by Regulation (EU) No 649/2012 concerning the export and import of dangerous chemicals:

| Name                                                              |                     |
|-------------------------------------------------------------------|---------------------|
| 4-nonylphenol, branched<br>CAS No: 84852-15-3<br>EC No: 284-325-5 |                     |
| Annex I Part 2 - Category                                         | Industrial chemical |
| It is not possible to export this chemical.                       |                     |

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

| Designation of the substance, of the group of substances or of the mixture                                                                            | Conditions of restriction                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 46.<br>(a) Nonylphenol<br><chem>C6H4(OH)C9H19</chem><br>CAS 25154-52-3<br>EC 246-672-0<br>(b) Nonylphenol ethoxylates<br><chem>(C2H4O)nC15H24O</chem> | Shall not be placed on the market, or used, as substances or in mixtures in concentrations equal to or greater than 0,1 % by weight for the following purposes:<br>(1) industrial and institutional cleaning except:<br>- controlled closed dry cleaning systems where the washing liquid is recycled or incinerated,<br>- cleaning systems with special treatment where the washing liquid is recycled or incinerated.<br>(2) domestic cleaning;<br>(3) textiles and leather processing except:<br>- processing with no release into waste water,<br>- systems with special treatment where the process water is pre-treated to remove the organic fraction completely prior to biological waste water treatment (degreasing of sheepskin);<br>(4) emulsifier in agricultural teat dips;<br>(5) metal working except:<br>uses in controlled closed systems where the washing liquid is recycled or incinerated;<br>(6) manufacturing of pulp and paper;<br>(7) cosmetic products;<br>(8) other personal care products except:<br>spermicides;<br>(9) co-formulants in pesticides and biocides. However national authorisations for pesticides or biocidal products containing nonylphenol ethoxylates as co-formulant, granted before 17 July 2003, shall not be affected by this restriction until their date of expiry. |
| 46a. Nonylphenol ethoxylates (NPE)<br><chem>(C2H4O)nC15H24O</chem>                                                                                    | 1. Shall not be placed on the market after 3 February 2021 in textile articles which can reasonably be expected to be washed in water during their normal lifecycle, in concentrations equal to or greater than 0,01 % by weight of that textile article or of each part of the textile article.<br>2. Paragraph 1 shall not apply to the placing on the market of second-hand textile articles or of new textile articles produced, without the use of NPE, exclusively from recycled textiles.<br>3. For the purposes of paragraphs 1 and 2, "textile article" means any unfinished, semi-finished or finished product which is composed of at least 80 % textile fibres by weight, or any other product that contains a part which is composed of at least 80 % textile fibres by weight, including products such as clothing, accessories, interior textiles, fibres, yarn, fabrics and knitted panels.                                                                                                                                                                                                                                                                                                                                                                                                                |

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## 1010011-RESINA ELASTICER



Version 1      Date of compilation: 5/07/2010

Version 12 (replaces version 11)

Revision date: 10/03/2026

Page 11 of 12

Print date: 10/03/2026

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

|        |                                                                          |
|--------|--------------------------------------------------------------------------|
| H302   | Harmful if swallowed.                                                    |
| H314   | Causes severe skin burns and eye damage.                                 |
| H315   | Causes skin irritation.                                                  |
| H317   | May cause an allergic skin reaction.                                     |
| H319   | Causes serious eye irritation.                                           |
| H360F  | May damage fertility.                                                    |
| H361fd | Suspected of damaging fertility. Suspected of damaging the unborn child. |
| H400   | Very toxic to aquatic life.                                              |
| H410   | Very toxic to aquatic life with long lasting effects.                    |
| H411   | Toxic to aquatic life with long lasting effects.                         |

Classification codes:

Acute Tox. 4: Acute toxicity (Oral), Category 4  
Aquatic Acute 1: Acute toxicity to the aquatic environment, Category 1  
Aquatic Chronic 1: Chronic effect to the aquatic environment, Category 1  
Aquatic Chronic 2: Chronic effect to the aquatic environment, Category 2  
Eye Irrit. 2: Eye irritation, Category 2  
Repr. 1B: Reproductive toxicant, Category 1B  
Repr. 2: Reproductive toxicant, Category 2  
Skin Corr. 1B: Skin Corrosive, Category 1B  
Skin Irrit. 2: Skin irritant, Category 2  
Skin Sens. 1: Skin sensitiser, Category 1

Changes regarding to the previous version:

- Change in the hazard classification (SECTION 2.1).
- Changes in the composition of the product (SECTION 3.2).
- Change in the hazard classification (SECTION 11.1).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

|                       |                       |
|-----------------------|-----------------------|
| Physical hazards      | On basis of test data |
| Health hazards        | Calculation method    |
| Environmental hazards | Calculation method    |

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

|       |                                                                                                                               |
|-------|-------------------------------------------------------------------------------------------------------------------------------|
| ADR:  | Agreement concerning the International Carriage of Dangerous Goods by Road.                                                   |
| CEN:  | European Committee for Standardization.                                                                                       |
| DMEL: | Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum. |
| DNEL: | Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.                  |
| PPE:  | Personal protection equipment.                                                                                                |
| IATA: | International Air Transport Association.                                                                                      |
| ICAO: | International Civil Aviation Organization.                                                                                    |
| IMDG: | International Maritime Code for Dangerous Goods.                                                                              |
| RID:  | Regulations Concerning the International Transport of Dangerous Goods by Rail.                                                |

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## 1010011-RESINA ELASTICER



**Version 1      Date of compilation: 5/07/2010**

**Version 12 (replaces version 11)**

**Revision date: 10/03/2026**

**Page 12 of 12**

**Print date: 10/03/2026**

Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## ENDURECEDOR ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 16 (replaces version 15)

Revision date: 16/06/2025

Page 1 of 11

Print date: 16/06/2025

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: ENDURECEDOR ELASTICER  
Product Code: 1010008

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against.

Not available.

#### 1.3 Details of the supplier of the safety data sheet.

Company: **FIXCER PRODUCTS, S.A.U.**  
Address: CTRA. SANT CUGAT KM. 3  
City: CERDANYOLA DEL VALLÈS  
Province: BARCELONA  
Telephone: 93 586 20 03  
Fax: 93 586 10 91  
E-mail: fixcer@fixcer.com  
Web: www.fixcer.com

**1.4 Emergency telephone number:** Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. (Available 24 hours)

### SECTION 2: HAZARDS IDENTIFICATION.

#### 2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Acute Tox. 4 : Harmful if swallowed.  
Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects.  
Eye Dam. 1 : Causes serious eye damage.  
Skin Corr. 1A : Causes severe skin burns and eye damage.  
Skin Sens. 1 : May cause an allergic skin reaction.

#### 2.2 Label elements.

##### Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:



Signal Word:

**Danger**

Hazard statements:

H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P264 Wash ... thoroughly after handling.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## ENDURECEDOR ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 16 (replaces version 15)

Revision date: 16/06/2025

Page 2 of 11

Print date: 16/06/2025

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/...

P321 Specific treatment (see ... on this label).

EUH statements:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Contains:

benzyl alcohol

2,4,6-tris(dimethylaminomethyl)phenol

3-aminomethyl-3,5,5-trimethylcyclohexylamine

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)

m-phenylenebis(methylamine)

Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer

### 2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

### 3.1 Substances.

Not applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

| Identifiers                                                                                               | Name                                                                                                                                         | Concentrate | (*)Classification - Regulation (EC) No 1272/2008                                      |                                                                        |
|-----------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|-------------|---------------------------------------------------------------------------------------|------------------------------------------------------------------------|
|                                                                                                           |                                                                                                                                              |             | Classification                                                                        | Specifics concentration limits and Acute toxicity estimate             |
| Index No: 603-057-00-5<br>CAS No: 100-51-6<br>EC No: 202-859-9<br>Registration No: 01-2119492630-38-XXXX  | benzyl alcohol                                                                                                                               | 1 - 50 %    | Acute Tox. 4, H302+H332                                                               | -                                                                      |
| CAS No: 68609-08-5                                                                                        | Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer                            | 5 - 50 %    | Eye Dam. 1, H318 - Skin Corr. 1B, H314                                                | -                                                                      |
| Index No: 612-067-00-9<br>CAS No: 2855-13-2<br>EC No: 220-666-8<br>Registration No: 01-2119514687-32-XXXX | 3-aminomethyl-3,5,5-trimethylcyclohexylamine                                                                                                 | 5 - 25 %    | Acute Tox. 4, H302 - Eye Dam. 1, H318 - Skin Corr. 1B, H314 - Skin Sens. 1, H317      | Skin Sens. 1A, H317: C ≥ 0,001 %<br>Oral: ETA = 1030 mg/kg pc (ATP 17) |
| CAS No: 113930-69-1<br>EC No: 500-302-7<br>Registration No: 01-2119965162-39-XXXX                         | 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine) | 5 - 25 %    | Aquatic Chronic 3, H412 - Eye Dam. 1, H318 - Skin Corr. 1B, H314 - Skin Sens. 1, H317 | -                                                                      |

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## ENDURECEDOR ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 16 (replaces version 15)

Revision date: 16/06/2025

Page 3 of 11

Print date: 16/06/2025

|                                                                                                         |                                       |           |                                                                           |   |
|---------------------------------------------------------------------------------------------------------|---------------------------------------|-----------|---------------------------------------------------------------------------|---|
| CAS No: 1477-55-0<br>EC No: 216-032-5<br>Registration No: 01-2119480150-50-XXXX                         | m-phenylenebis(methylamine)           | 5 - 25 %  | Acute Tox. 4,<br>H302 - Skin<br>Corr. 1A, H314<br>- Skin Sens. 1,<br>H317 | - |
| Index No: 603-069-00-0<br>CAS No: 90-72-2<br>EC No: 202-013-9<br>Registration No: 01-2119560597-27-XXXX | 2,4,6-tris(dimethylaminomethyl)phenol | 1 - 10 %  | Acute Tox. 4,<br>H302                                                     | - |
| CAS No: 71074-89-0<br>EC No: 275-162-0                                                                  | bis[(dimethylamino)methyl]phenol      | 0.1 - 1 % | Acute Tox. 3,<br>H311                                                     | - |

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

### SECTION 4: FIRST AID MEASURES.

#### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

#### Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

#### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners. The use of personal protective equipment is recommended for people providing first aid (see section 8).

#### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

Contact with eyes may cause irreversible damage.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract.

### SECTION 5: FIREFIGHTING MEASURES.

The product is NOT classified as flammable, in case of fire the following measures should be taken:

#### 5.1 Extinguishing media.

##### Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

##### Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## ENDURECEDOR ELASTICER



Version 1      Date of compilation: 5/07/2010

Version 16 (replaces version 15)

Revision date: 16/06/2025

Page 4 of 11

Print date: 16/06/2025

### 5.2 Special hazards arising from the substance or mixture.

#### **Special risks.**

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- NO<sub>x</sub> (nitrogen oxides).

### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

#### **Fire protection equipment.**

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

## SECTION 6: ACCIDENTAL RELEASE MEASURES.

### 6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

### 6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

### 6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

## SECTION 7: HANDLING AND STORAGE.

### 7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

### 7.3 Specific end use(s).

Not available.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## ENDURECEDOR ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 16 (replaces version 15)

Revision date: 16/06/2025

Page 5 of 11

Print date: 16/06/2025

### 8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

| Name                                                                         | DNEL/DMEL         | Type                                  | Value                        |
|------------------------------------------------------------------------------|-------------------|---------------------------------------|------------------------------|
| benzyl alcohol<br>CAS No: 100-51-6<br>EC No: 202-859-9                       | DNEL<br>(Workers) | Inhalation, Chronic, Systemic effects | 90<br>(mg/m <sup>3</sup> )   |
| 2,4,6-tris(dimethylaminomethyl)phenol<br>CAS No: 90-72-2<br>EC No: 202-013-9 | DNEL<br>(Workers) | Inhalation, Chronic, Systemic effects | 0,31<br>(mg/m <sup>3</sup> ) |

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

|                              |                                                                                                                                                                                                                                                                                                           |                           |       |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|-------|
| <b>Concentration:</b>        | <b>100 %</b>                                                                                                                                                                                                                                                                                              |                           |       |
| <b>Uses:</b>                 |                                                                                                                                                                                                                                                                                                           |                           |       |
| <b>Breathing protection:</b> |                                                                                                                                                                                                                                                                                                           |                           |       |
| PPE:                         | Filter mask for protection against gases and particles.                                                                                                                                                                                                                                                   |                           |       |
| Characteristics:             | «CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.                                                                                                                                                             |                           |       |
| CEN standards:               | EN 136, EN 140, EN 405                                                                                                                                                                                                                                                                                    |                           |       |
| Maintenance:                 | Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.                                                                                                  |                           |       |
| Observations:                | Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer. |                           |       |
| Filter Type needed:          | A2                                                                                                                                                                                                                                                                                                        |                           |       |
| <b>Hand protection:</b>      |                                                                                                                                                                                                                                                                                                           |                           |       |
| PPE:                         | Protective gloves against chemicals.                                                                                                                                                                                                                                                                      |                           |       |
| Characteristics:             | «CE» marking, category III.                                                                                                                                                                                                                                                                               |                           |       |
| CEN standards:               | EN 374-1, En 374-2, EN 374-3, EN 420                                                                                                                                                                                                                                                                      |                           |       |
| Maintenance:                 | Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.                                                                                    |                           |       |
| Observations:                | Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.                                                                                                                                                                |                           |       |
| Material:                    | PVC (polyvinyl chloride)                                                                                                                                                                                                                                                                                  | Breakthrough time (min.): | > 480 |
|                              |                                                                                                                                                                                                                                                                                                           | Material thickness (mm):  | 0,35  |
| <b>Eye protection:</b>       |                                                                                                                                                                                                                                                                                                           |                           |       |
| PPE:                         | Protective goggles with built-in frame.                                                                                                                                                                                                                                                                   |                           |       |
| Characteristics:             | «CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.                                                                                                                                                                                          |                           |       |
| CEN standards:               | EN 165, EN 166, EN 167, EN 168                                                                                                                                                                                                                                                                            |                           |       |
| Maintenance:                 | Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.                                                                                                                       |                           |       |
| Observations:                | Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.                                                                                                                                                                                  |                           |       |
| <b>Skin protection:</b>      |                                                                                                                                                                                                                                                                                                           |                           |       |
| PPE:                         | Chemical protective clothing                                                                                                                                                                                                                                                                              |                           |       |
| Characteristics:             | «CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.                                                               |                           |       |
| CEN standards:               | EN 464, EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034                                                                                                                                                                                                                                    |                           |       |

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## ENDURECEDOR ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 16 (replaces version 15)

Revision date: 16/06/2025

Page 6 of 11

Print date: 16/06/2025

|                  |                                                                                                                                                                                                                                                                         |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Maintenance:     | In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.                                                                                                                                                 |
| Observations:    | The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity. |
| PPE:             | Anti-static safety footwear against chemicals.                                                                                                                                                                                                                          |
| Characteristics: | «CE» marking, category III. Check the list of chemicals against which the footwear is resistant.                                                                                                                                                                        |
| CEN standards:   | EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO 20345                                                                                                                                                                                            |
| Maintenance:     | For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is observed.                                                          |
| Observations:    | The footwear should be cleaned regularly and dried when damp, although it should not be placed too close to a source of heat in order to avoid any sharp changes in temperature.                                                                                        |



### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

#### 9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: Not applicable/Not available due to the nature/properties of the product

Odour: Not applicable/Not available due to the nature/properties of the product

Odour threshold: Not applicable/Not available due to the nature/properties of the product

Melting point: Not applicable/Not available due to the nature/properties of the product

Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: Not applicable/Not available due to the nature/properties of the product

Flammability: Not applicable/Not available due to the nature/properties of the product

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product

Upper explosion limit: Not applicable/Not available due to the nature/properties of the product

Flash point: > 60 °C

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product

Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

pH: Not applicable (Substance/mixture is non-soluble (in water)).

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product

Solubility: Not applicable/Not available due to the nature/properties of the product

Hydrosolubility: Not applicable/Not available due to the nature/properties of the product

Liposolubility: Not applicable/Not available due to the nature/properties of the product

Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product

Vapour pressure: Not applicable/Not available due to the nature/properties of the product

Absolute density: Not applicable/Not available due to the nature/properties of the product

Relative density: Not applicable/Not available due to the nature/properties of the product

Relative vapour density: Not applicable/Not available due to the nature/properties of the product

Particle characteristics: Not applicable/Not available due to the nature/properties of the product

#### 9.2 Other information

Not applicable/Not available due to the nature/properties of the product

### SECTION 10: STABILITY AND REACTIVITY.

#### 10.1 Reactivity.

The product does not present hazards by their reactivity.

#### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

#### 10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

#### 10.4 Conditions to avoid.

Avoid any improper handling.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## ENDURECEDOR ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 16 (replaces version 15)

Revision date: 16/06/2025

Page 7 of 11

Print date: 16/06/2025

### 10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

### 10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

## SECTION 11: TOXICOLOGICAL INFORMATION.

### 11.1 Information on hazard classes as defined in Regulation (EC) N° 1272/2008.

There are no tested data available on the product.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;

Product classified:

Acute toxicity (Oral), Category 4: Harmful if swallowed.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Dermal) = 40.000 mg/kg

ATE (Oral) = 832 mg/kg

b) skin corrosion/irritation;

Product classified:

Skin Corrosive, Category 1A: Causes severe skin burns and eye damage.

c) serious eye damage/irritation;

Product classified:

Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

### 11.2 Information on other hazards.

#### Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

#### Other information

There is no information available on other adverse health effects.

## SECTION 12: ECOLOGICAL INFORMATION.

### 12.1 Toxicity.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## ENDURECEDOR ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 16 (replaces version 15)

Revision date: 16/06/2025

Page 8 of 11

Print date: 16/06/2025

No information is available regarding the ecotoxicity of the substances present.

### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

### 12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

| Name                                                | Bioaccumulation |     |       |          |
|-----------------------------------------------------|-----------------|-----|-------|----------|
|                                                     | Log Pow         | BCF | NOECs | Level    |
| benzyl alcohol<br>CAS No: 100-51-6 EC No: 202-859-9 | 1,05            | -   | -     | Very low |

### 12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

### 12.7 Other adverse effects.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

No information is available about other adverse effects for the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS.

### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

## SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

**Sea:** Transport by ship: IMDG.

Transport documentation: Bill of lading

**Air:** Transport by plane: ICAO/IATA.

Transport document: Airway bill.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## ENDURECEDOR ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 16 (replaces version 15)

Revision date: 16/06/2025

Page 9 of 11

Print date: 16/06/2025

### 14.1 UN number or ID number.

UN No: UN2735

### 14.2 UN proper shipping name.

Description:

ADR/RID: UN 2735, AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS CYCLOHEXANEMETHANAMINE, 5-AMINO-1,3,3-TRIMETHYL-, REACTION PRODUCTS WITH BISPHENOL A DIGLYCIDYL ETHER HOMOPOLYMER / 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE), 8, PG III, (E)

IMDG: UN 2735, AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS CYCLOHEXANEMETHANAMINE, 5-AMINO-1,3,3-TRIMETHYL-, REACTION PRODUCTS WITH BISPHENOL A DIGLYCIDYL ETHER HOMOPOLYMER / 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE), 8, PG III

ICAO/IATA: UN 2735, AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS CYCLOHEXANEMETHANAMINE, 5-AMINO-1,3,3-TRIMETHYL-, REACTION PRODUCTS WITH BISPHENOL A DIGLYCIDYL ETHER HOMOPOLYMER / 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE), 8, PG III

### 14.3 Transport hazard class(es).

Class(es): 8

### 14.4 Packing group.

Packing group: III

### 14.5 Environmental hazards.

Marine pollutant: No

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-B

### 14.6 Special precautions for user.

Labels: 8



Hazard number: 80

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Proceed in accordance with point 6.

IMDG Code segregation group: 18 Alkalis

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 1 L

### 14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

## SECTION 15: REGULATORY INFORMATION.

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Volatile organic compound (VOC)

VOC content (p/p): 54,125 %

VOC content: 548,898 g/l

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## ENDURECEDOR ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 16 (replaces version 15)

Revision date: 16/06/2025

Page 10 of 11

Print date: 16/06/2025

| Designation of the substance, of the group of substances or of the mixture                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Conditions of restriction                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 3. Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008:<br>(a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;<br>(b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;<br>(c) hazard class 4.1;<br>(d) hazard class 5.1. | 1. Shall not be used in:<br>- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,<br>- tricks and jokes,<br>- games for one or more participants, or any article intended to be used as such, even with ornamental aspects,<br>2. Articles not complying with paragraph 1 shall not be placed on the market.<br>3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:<br>- can be used as fuel in decorative oil lamps for supply to the general public, and,<br>- present an aspiration hazard and are labelled with H304,<br>4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).<br>5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:<br>(a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: 'Keep lamps filled with this liquid out of the reach of children'; and, by 1 December 2010, 'Just a sip of lamp oil - or even sucking the wick of lamps - may lead to life-threatening lung damage';<br>(b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter may lead to life threatening lung damage';<br>(c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010. |

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16: OTHER INFORMATION.

Classification codes:

Acute Tox. 3 : Acute toxicity (Dermal), Category 3  
Acute Tox. 4 : Acute toxicity (Inhalation), Category 4  
Acute Tox. 4 : Acute toxicity (Oral), Category 4  
Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2  
Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3  
Eye Dam. 1 : Serious eye damage, Category 1  
Eye Irrit. 2 : Eye irritation, Category 2  
Skin Corr. 1A : Skin Corrosive, Category 1A  
Skin Corr. 1B : Skin Corrosive, Category 1B  
Skin Irrit. 2 : Skin irritant, Category 2  
Skin Sens. 1 : Skin sensitiser, Category 1  
Skin Sens. 1A : Skin sensitiser, Category 1A  
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

|                       |                       |
|-----------------------|-----------------------|
| Physical hazards      | On basis of test data |
| Health hazards        | Calculation method    |
| Environmental hazards | Calculation method    |

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## ENDURECEDOR ELASTICER



**Version 1      Date of compilation: 5/07/2010**

**Version 16 (replaces version 15)**

**Revision date: 16/06/2025**

**Page 11 of 11**

**Print date: 16/06/2025**

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

### Abbreviations and acronyms used:

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.  
BCF: Bioconcentration factor.  
CEN: European Committee for Standardization.  
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.  
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.  
EC50: Half maximal effective concentration.  
PPE: Personal protection equipment.  
IATA: International Air Transport Association.  
ICAO: International Civil Aviation Organization.  
IMDG: International Maritime Code for Dangerous Goods.  
LC50: Lethal concentration, 50%.  
LD50: Lethal dose, 50%.  
NOEC: No observed effect concentration.  
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

### Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.