

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

SELLALASTIC



Version 1 Date of compilation: 31/03/2016

Version 2 (replaces version 1)

Revision date: 16/03/2023

Page 1 of 10

Print date: 24/03/2023

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: SELLALASTIC
Product Code: SE

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Sellador para la industria de la construcción

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **FIXCER PRODUCTS, S.A.U.**
Address: CTRA. SANT CUGAT KM. 3
City: CERDANYOLA DEL VALLÈS
Province: BARCELONA
Telephone: 93 586 20 03
Fax: 93 586 10 91
E-mail: fixcer@fixcer.com
Web: www.fixcer.com

1.4 Emergency telephone number: Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. (Available 24 hours)
Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420.
Información en español (24h/365 días). Únicamente con la finalidad de proporcionar respuesta sanitaria en caso de urgencia.

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

The product is not classified as hazardous within the meaning of Regulation (EC) No 1272/2008.

2.2 Label elements.

Precautionary statements:

P232 Protect from moisture.
P235 Keep cool.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

EUH statements:

EUH204 Contains isocyanates. May produce an allergic reaction.
EUH210 Safety data sheet available on request.

2.3 Other hazards.

The mixture does not contain substances classified as PBT.
The mixture does not contain substances classified as vPvB.
The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

SELLALASTIC



Version 1 Date of compilation: 31/03/2016

Version 2 (replaces version 1)

Revision date: 16/03/2023

Page 2 of 10

Print date: 24/03/2023

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 601-022-00-9 CAS No: 1330-20-7 EC No: 215-535-7 Registration No: 01-2119488216-32-XXXX	[1] [2] xylene	0 - 12.5 %	-	-
CAS No: 1305-78-8 EC No: 215-138-9 Registration No: 01-2119475325-36-XXXX	[1] [2] calcium oxide	0 - 5 %	-	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a European Union exposure limit in the workplace (see section 8.1).

[2] Substance with a national workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

Due to the composition and type of the substances present in the product, no particular warnings are necessary.

Inhalation.

If breathing stops, give artificial respiration and seek immediate medical attention. Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing.

Ingestion.

Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

No known acute or delayed effects from exposure to the product.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

SELLALASTIC



Version 1 Date of compilation: 31/03/2016

Version 2 (replaces version 1)

Revision date: 16/03/2023

Page 3 of 10

Print date: 24/03/2023

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The product does not require special handling measures, the following general measures are recommended:

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

The product does not require special storage measures. As general storage measures, sources of heat, radiation, electricity and contact with food should be avoided.

Keep away from oxidising agents and from highly acidic or alkaline materials.

Store the containers between 5 and 25 °C, in a dry and well-ventilated place.

Store according to local legislation. Observe indications on the label. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

-

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
------	---------	---------	-------------	-----	-------------------

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

SELLALASTIC



Version 1 Date of compilation: 31/03/2016

Version 2 (replaces version 1)

Revision date: 16/03/2023

Page 4 of 10

Print date: 24/03/2023

xylene	1330-20-7	España [1]	Eight hours	50(vía dérmica, sensibilizante)	221(vía dérmica, sensibilizante)
			Short term	100(vía dérmica, sensibilizante)	442(vía dérmica, sensibilizante)
		European Union [2]	Eight hours	50 (skin)	221 (skin)
			Short term	100 (skin)	442 (skin)
		United Kingdom [3]	Eight hours	50	220
			Short term	100	441
		Éire [4]	Eight hours	50	221
			Short term	100	442
		United States [5] (Cal/OSHA)	Eight hours	100	
			Short term	150 (Ceiling) 300	
calcium oxide	1305-78-8	España [1]	Eight hours		1 (Fracción respirable)
			Short term		4 (Fracción respirable)
		European Union [2]	Eight hours		1 (Respirable fraction)
			Short term		4 (Respirable fraction)
		United Kingdom [3]	Eight hours		2
			Short term		
		Éire [4]	Eight hours		1 (Respirable fraction)
			Short term		4 (Respirable fraction)
		United States [5] (Cal/OSHA)	Eight hours		2
			Short term		
		United States [6] (NIOSH)	Eight hours		2
			Short term		
		United States [7] (OSHA)	Eight hours		5
			Short term		

Biological exposure limit values for:

Name	CAS No.	Country	Biological indicator	BLV	Sampling time
xylene	1330-20-7	España [1]	Ácidos metilhipúricos en orina	1 g/g creatinina	Final de la jornada laboral

[1] Según la lista de Valores Límite Ambientales de Exposición Profesional adoptados por el Instituto Nacional de Seguridad y Salud en el Trabajo (INSST) para el año 2022.

[2] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[3] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[4] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

[5] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[6] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[7] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

Concentration levels DNEL/DMEL:

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

SELLALASTIC



Version 1 Date of compilation: 31/03/2016

Version 2 (replaces version 1)

Revision date: 16/03/2023

Page 5 of 10

Print date: 24/03/2023

Name	DNEL/DMEL	Type	Value
xylene CAS No: 1330-20-7 EC No: 215-535-7	DNEL (Workers)	Inhalation, Chronic, Systemic effects	77 (mg/m ³)
calcium oxide CAS No: 1305-78-8 EC No: 215-138-9	DNEL (Workers)	Inhalation, Chronic, Local effects	3,5 (mg/m ³)
	DNEL (Workers)	Inhalation, Chronic, Systemic effects	3,5 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	Sellador para la industria de la construcción		
Breathing protection:			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
Hand protection:			
PPE:	Protective gloves against chemicals.		
Characteristics:	«CE» marking, category III.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
Eye protection:			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		
Skin protection:			
PPE:	Protective clothing.		
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.		
CEN standards:	EN 340		
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.		
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.		
PPF:	Work footwear		

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

SELLALASTIC



Version 1 Date of compilation: 31/03/2016

Version 2 (replaces version 1)

Revision date: 16/03/2023

Page 6 of 10

Print date: 24/03/2023

Characteristics:	«CE» marking, category II.
CEN standards:	EN ISO 13287, EN 20347
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Solid

Colour: Not applicable/Not available due to the nature/properties of the product

Odour: Not applicable/Not available due to the nature/properties of the product

Odour threshold: Not applicable/Not available due to the nature/properties of the product

Melting point: Not applicable/Not available due to the nature/properties of the product

Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: Not applicable/Not available due to the nature/properties of the product

Flammability: Not applicable/Not available due to the nature/properties of the product

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product

Upper explosion limit: Not applicable/Not available due to the nature/properties of the product

Flash point: ≥ 40 °C

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product

Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

pH: Not applicable/Not available due to the nature/properties of the product

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product

Solubility: Not applicable/Not available due to the nature/properties of the product

Hydrosolubility: Not applicable/Not available due to the nature/properties of the product

Liposolubility: Not applicable/Not available due to the nature/properties of the product

Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product

Vapour pressure: Not applicable/Not available due to the nature/properties of the product

Absolute density: Not applicable/Not available due to the nature/properties of the product

Relative density: 1.323

Relative vapour density: Not applicable/Not available due to the nature/properties of the product

Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Not applicable/Not available due to the nature/properties of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

SELLALASTIC



Version 1 Date of compilation: 31/03/2016

Version 2 (replaces version 1)

Revision date: 16/03/2023

Page 7 of 10

Print date: 24/03/2023

11.1 Information on hazard classes as defined in Regulation (EC) N° 1272/2008.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
xylene	Oral	LD50	Rat	4300 mg/kg bw [1]
		[1] AMA Archives of Industrial Health. Vol. 14, Pg. 387, 1956		
	Dermal	LD50	Rabbit	> 1700 mg/kg bw [1]
		[1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974		
CAS No: 1330-20-7 EC No: 215-535-7	Inhalation	LC50	Rat	21,7 mg/l/4 h [1]
		[1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974		

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation;

Not conclusive data for classification.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
xylene	Fish	LC50	Fish	15,7 mg/l (96 h) [1]

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

SELLALASTIC



Version 1 Date of compilation: 31/03/2016

Version 2 (replaces version 1)

Revision date: 16/03/2023

Page 8 of 10

Print date: 24/03/2023

CAS No: 1330-20-7 EC No: 215-535-7		[1] Bailey, H.C., D.H.W. Liu, and H.A. Javitz 1985. Time/Toxicity Relationships in Short-Term Static, Dynamic, and Plug-Flow Bioassays. In: R.C.Bahner and D.J.Hansen (Eds.), Aquatic Toxicology and Hazard Assessment, 8th Symposium, ASTM STP 891, Philadelphia, PA :193-212
	Aquatic invertebrates	LC50 Crustacean 8,5 mg/l (48 h) [1] [1] Tatem, H.E., B.A. Cox, and J.W. Anderson 1978. The Toxicity of Oils and Petroleum Hydrocarbons to Estuarine Crustaceans. Estuar.Coast.Mar.Sci. 6(4):365-373. Tatem, H.E. 1975. The Toxicity and Physiological Effects of Oil and Petroleum Hydrocarbons on Estuarine Grass Shrimp Palaemonetes pugio (Holthuis). Ph.D.Thesis, Texas A&M University, College Station, TX :133 p
	Aquatic plants	

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

SELLALASTIC



Version 1 Date of compilation: 31/03/2016

Version 2 (replaces version 1)

Revision date: 16/03/2023

Page 9 of 10

Print date: 24/03/2023

14.1 UN number or ID number.

Transportation is not dangerous.

14.2 UN proper shipping name.

Description:

ADR/RID: Not classified as hazardous for transport.

IMDG: Not classified as hazardous for transport.

ICAO/IATA: Not classified as hazardous for transport.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): Not applicable.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Maritime transport in bulk according to IMO instruments.

Transportation is not dangerous.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

VOC content (p/p): 0,99 %

VOC content: 13,098 g/l

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4

Acute Tox. 4 : Acute toxicity (Inhalation), Category 4

Eye Dam. 1 : Serious eye damage, Category 1

Flam. Liq. 3 : Flammable liquid, Category 3

STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Skin Irrit. 2 : Skin irritant, Category 2

Changes regarding to the previous version:

- Change of the name of the product (SECTION 1.1).

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

SELLALASTIC



Version 1 Date of compilation: 31/03/2016

Version 2 (replaces version 1)

Revision date: 16/03/2023

Page 10 of 10

Print date: 24/03/2023

- Change of the uses of the product (SECTION 1.2).
- Changes in the information of the supplier (SECTION 1.3).
- Change in the emergency number (SECTION 1.4).
- Addition of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Modification of specific hazards (SECTION 2.3).
- Changes in the composition of the product (SECTION 3.2).
- Modifications in the first aid measures (SECTION 4.1).
- Modification in the firefighting measures (SECTION 5.2).
- Modifications in the accidental release measures (SECTION 6.1).
- Modifications in the accidental release measures (SECTION 6.3).
- Change of the uses of the product (SECTION 7.3).
- Addition of exposure data (SECTION 8.1).
- Addition of personal protective equipment (SECTION 8.2).
- Modifications of the personal protective equipment (SECTION 8.2).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Addition of ecotoxicity values (SECTION 11.1).
- Change in the hazard classification (SECTION 11.1).
- Addition of ecological information values (SECTION 12.1).
- Addition of classification ADR/IMDG/ICAO/IATA/RID (SECTION 14).
- National legislative changes (SECTION 15.1).
- Addition of abbreviations and acronyms (SECTION 16).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is recommended that the product only be employed for the purposes advised.

Abbreviations and acronyms used:

CEN:	European Committee for Standardization.
DMEL:	Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL:	Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50:	Half maximal effective concentration.
PPE:	Personal protection equipment.
LC50:	Lethal concentration, 50%.
LD50:	Lethal dose, 50%.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.