

FIX-BANDA DRAIN

Self-adhesive waterproofing tape to ensure watertightness in DRAINS, before to the application of waterproofing.



HOW TO USE

SUPPORT PREPARATION

- The substrate must be resistant, dust-free and perfectly set.
- Fragile or very porous surfaces must be pre-treated with **PRIMFIX** or **IMPRIMACION SELLADOR S10** and left to dry for at least 1 hour.

PRODUCT PREPARATION

- FIX-BANDA DRAIN** is a ready-to-use product.

The support must be solid, clean and dry



Place the sheet in the center of the sump to be sealed



Fold the sheet into two parts following the pre-cut



Remove the protective paper from only one of the two parts.



Glue the sheet and press hard to get a total grip.




Fold the sheet on the other side of the pre-cut.



Remove the paper of this side; glue it and press hard.



Take a blade and make V cuts from the center to the perimeter.




The cuts should start at the perimeter and should reach the center of the drain.




Cut the entire sheet completely discovering the sump.



Paste the sheet neatly into the walls of the sump, and with it...



...we will have the surface ready to receive the waterproofing.



TECHNICAL DATA

Type of fibre	polyester
Impermeability	100%
Mass per cm ³	1.4 g/cm ³
Type of butyl	butil-poliisobutileno
Temperature of application	from +50°C to +40°C
Resistance to slipping of butyl	< 5 mm
Maximum longitudinal elongation	> 70%
Maximum transverse elongation	> 70%
Shear adhesion (90°)	> 70 N
Resistance to temperature	from -30°C to +80°C
Consumption	1 drain / 1 unit
Estimated expiration	unlimited
Presentation	sheets of 0.40 x 0.40 m

MAIN FEATURES

- FIX-BANDA DRAIN** is composed of a viscoelastic layer of butyl rubber, coated with a non-woven of polyester fibres that allows the sheet to deform in both directions.
- It is compatible with most substrates: aluminium, glass, concrete and mortar.
- Not compatible with asphalt.**
- Self-adhesive band.
- Waterproof.
- Measurements 40 x 40 cm.

FIELDS OF APPLICATION

- Ideal for ensuring watertightness in drains before to the application of **FIX-TERRATS FIBRE**, **FIXAQUA FILM**, **HIDROELASTIC**, **HIDROFACIL** or **HIDRO-FIX**.
- Ideal for terraces, balconies, decks and swimming pool decks.

