

FIX-GRAF STONE

Paint thinner for removing graffiti, paint and rubbers from coarse surfaces NOT PREVIOUSLY TREATED with anti-graffiti products. Useful for removing epoxy residues.



MAIN FEATURES

- FIX-GRAF STONE** is a HIGHLY concentrated mixture of solvents and paint strippers, specially formulated for all intensive cleaning jobs.
- FIX-GRAF STONE** should only be applied with intense ventilation.
- FIX-GRAF STONE** should not be used without the necessary precautions.

FIELDS OF APPLICATION

- Removal of graffiti and/or paint residues on porous horizontal and vertical surfaces such as stoneware floors, concrete walls, plaster, natural stone cladding, granite, marble, ceramics, etc.
- Removal of dry residues of **CERPOXI**. For stubborn cases apply as many times as necessary.
- Applicable indoors and outdoors, both vertically and horizontally.

HOW TO USE

PRODUCT PREPARATION

- FIX-GRAF STONE** is a ready-to-use product.

PRODUCT APPLICATION

- Apply by brush a uniform coat of the undiluted product leaving it to act usually for 5 to 10 minutes to remove graffiti and from 12 to 24 hours to remove epoxy residues.
- A second coat can be applied if it is necessary.
- Subsequently carry out a deep cleaning with pressurised water or by brushing.

COMMENTS TO TAKE INTO ACCOUNT

- Do not use it to remove stains on painted surfaces whose original paintwork you wish to preserve.
- Do not use it on shiny surfaces such as polished marble.
- Do not use it without taking all the necessary personal precautions: gloves, goggles,...

TECHNICAL DATA

Type of product	stripper
Colour	green
Density	1.15 g/cm ³
pH	2.5
Water solubility	100%
Suitable for	indoor and outdoor
Flammability	yes
Toxicity	irritating
Self-protection measures	goggles, mask and gloves
Temperature of application	from +0°C to +80°C
Proportion of mix	pure
Consumption	0.2 L/m ² per coat
Estimated expiration	36 months
Presentation	1 L and 25 L

