

# FIX-WALL

**COLOURLESS treatment with a hydro-repellent effect for vertical surfaces of facing brick, concrete, sandstone, renders...**

## What can be expected of FIX-WALL?

- ◆ **FIX-WALL** is a façade waterproofer.
- ◆ **FIX-WALL** prevents the rain from soaking the façade and seeping into the house.
- ◆ There can be no doubt: if it rains today, and tomorrow the inside of the house is damp, it is necessary to apply **FIX-WALL** to the exterior of the façade.
- ◆ With 2 or 3 coats of **FIX-WALL**, total protection against rainwater is achieved.



## ATTENTION

**FIX-WALL** should not be used:

- ◆ For natural, glazed or polished porcelain tiles.
- ◆ On water tanks.
- ◆ On exterior basement walls (use **HIDROFIX**)

## COVERAGE:

**FIX-WALL** 0.8 l/m<sup>2</sup> (applying 2 consecutive saturating coats)



## INSTRUCTIONS FOR USE:

1



Without protection, facing brick absorbs rainwater, which will end up seeping inside.

2



Apply 2 coats of **FIX-WALL** using a varnish roller (let dry for 24 hours between coats).

3



With **FIX-WALL**, the water turns into little drops on the surface, which end up sliding downwards.