(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1 Date of compilation: 5/07/2010 Version 8 (replaces version 7) Revision date: 16/03/2023 Page 1 of 30 Print date: 24/03/2023

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: Product Code: RESINA ELASTICER 1010011

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Not available.

Company.

**Uses advised against:** Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

### FIXCER PRODUCTS, S.A.U.

Address:	CTRA. SANT CUGAT KM. 3
City:	CERDANYOLA DEL VALLÈS
Province:	BARCELONA
Telephone:	93 586 20 03
Fax:	93 586 10 91
E-mail:	fixcer@fixcer.com
Web:	www.fixcer.com

**1.4 Emergency telephone number:** Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. (Available 24 hours)

Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. Información en español (24h/365 días). Únicamente con la finalidad de proporcionar respuesta sanitaria en caso de urgencia.

### **SECTION 2: HAZARDS IDENTIFICATION.**

#### 2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008: Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects. Eye Irrit. 2 : Causes serious eye irritation. Skin Irrit. 2 : Causes skin irritation. Skin Sens. 1 : May cause an allergic skin reaction.

#### 2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008: Pictograms:



Hazard statements:

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.

(in accordance with Regulation (EU) 2020/878)

## **ELASTICER**



Version 1	Version 1 Date of compilation: 5/07/2010			
		Revision date: 16/03/2023		

Page 2 of 30 Print date: 24/03/2023

P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/
P321	Specific treatment (see on this label).
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container to

#### EUH statements: EUH205

Contains epoxy constituents. May produce an allergic reaction.

#### Contains:

bis-[4-(2,3-epoxipropoxi)phenyl]propane oxirane, mono[(C12-14-alkyloxy)methyl] derivs. Cashew, nutshell liq. Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

#### 2.3 Other hazards.

The mixture does not contain substances classified as PBT. The mixture does not contain substances classified as vPvB. The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

#### 3.1 Substances.

Not Applicable.

#### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
Identifiers			Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 603-103- 00-4 CAS No: 68609-97-2 EC No: 271-846-8 Registration No: 01- 2119485289-22-XXXX	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	10 - 25 %	Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
Index No: 603-073- 00-2 CAS No: 1675-54-3 EC No: 216-823-5	bis-[4-(2,3-epoxipropoxi)phenyl]propane	5 - 25 %	Eye Irrit. 2, H319 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	Eye Irrit. 2, H319: C ≥ 5 % Skin Irrit. 2, H315: C ≥ 5 %
CAS No: 9003-36-5 EC No: 500-006-8 Registration No: 01- 2119454392-40-XXXX	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	2.5 - 10 %	Aquatic Chronic 3, H412 - Skin Sens. 1, H317	-
CAS No: 8007-24-7 EC No: 232-355-4 Registration No: 01- 2120038044-68-XXXX	Cashew, nutshell liq.	1 - 3 %	Acute Tox. 4, H302 - Eye Irrit. 2, H319 - Skin Sens. 1, H317	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

### **SECTION 4: FIRST AID MEASURES.**

(in accordance with Regulation (EU) 2020/878)

## **ELASTICER**



#### Version 1 Date of compilation: 5/07/2010

Version 8 (replaces version 7) Revision date: 16/03/2023

Page 3 of 30 Print date: 24/03/2023

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

#### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

#### Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

#### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

#### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

### **SECTION 5: FIREFIGHTING MEASURES.**

The product is NOT classified as flammable, in case of fire the following measures should be taken:

#### 5.1 Extinguishing media.

#### Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

#### Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

#### 5.2 Special hazards arising from the substance or mixture.

#### Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

#### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

#### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES.**

#### 6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

#### 6.2 Environmental precautions.

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 8 (replaces version 7) Revision date: 16/03/2023

Page 4 of 30 Print date: 24/03/2023

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

#### 6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

#### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

### **SECTION 7: HANDLING AND STORAGE.**

#### 7.1 Precautions for safe handling.

For personal protection, see section 8. In the application area, smoking, eating, and drinking must be prohibited. Follow legislation on occupational health and safety. Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

#### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and wellventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

#### 7.3 Specific end use(s).

Not available.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

#### 8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values. Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
avirana mana[(C12,14, alla dava) mathud] daviva	DNEL	Inhalation, Chronic, Local effects	0,98
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. CAS No: 68609-97-2	(Workers)		(mg/m <sup>3</sup> )
EC No: 271-846-8	DNEL	Inhalation, Chronic, Systemic effects	13,8
EC NO: 271-040-0	(Workers)		(mg/m <sup>3</sup> )

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated. DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

#### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %	
Uses:		
Breathing protection:		
PPE:	Filter mask for protection against gases and particles.	

(in accordance with Regulation (EU) 2020/878)

### **ELASTICER**



Version 1 Dat Version 8 (replace	te of compilation: 5/07/2010 Page 5 of 30 es version 7) Revision date: 16/03/2023 Print date: 24/03/2023
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.
CEN standards:	EN 136, EN 140, EN 405
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach
Observations:	the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.
Filter Type needed:	A2
Hand protection:	Diretactiva alavas against shamiasla
PPE: Characteristics:	Protective gloves against chemicals. «CE» marking, category III.
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.
Material:	PVC (polyvinyl chloride) Breakthrough time (min.): > 480 Material thickness (mm): 0,35
Eye protection:	
PPE:	Protective goggles with built-in frame.
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.
CEN standards:	EN 165, EN 166, EN 167, EN 168
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.
Skin protection:	
PPE:	Chemical protective clothing
Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.
CEN standards:	EN 464,EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.
PPE:	Anti-static safety footwear against chemicals.
Characteristics:	«CE» marking, category III. Check the list of chemicals against which the footwear is resistant.
CEN standards:	EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO 20345
Maintenance:	For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is observed.
Observations:	The footwear should be cleaned regularly and dried when damp, although it should not be placed too close to a source of heat in order to avoid any sharp changes in temperature.

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.**

### **9.1 Information on basic physical and chemical properties.** Physical state: Liquid

Physical state: Liquid Colour: Not applicable/Not available due to the nature/properties of the product Odour: Not applicable/Not available due to the nature/properties of the product Odour threshold: Not applicable Melting point: Not applicable Freezing point: Not applicable Boiling point or initial boiling point and boiling range: Not applicable

(in accordance with Regulation (EU) 2020/878)

## **ELASTICER**



Version 1Date of compilation: 5/07/2010Version 8 (replaces version 7)Revision date: 16/03/2023

Page 6 of 30 Print date: 24/03/2023

Flammability: Not applicable Lower explosion limit: Not applicable Upper explosion limit: Not applicable Flash point: Not applicable Auto-ignition temperature: Not applicable Decomposition temperature: Not applicable pH: Not applicable (Substance/mixture is non-soluble (in water)). Kinematic viscosity: Not applicable Solubility: Not applicable Hydrosolubility: Not applicable Liposolubility: Not applicable Partition coefficient n-octanol/water (log value): Not applicable Vapour pressure: Not applicable Absolute density: Not applicable Relative density: Not applicable Relative vapour density: Not applicable Particle characteristics: Not applicable

#### 9.2 Other information

Other safety characteristics Viscosity: Not applicable Dropping point: Not applicable Blink: Not applicable

### SECTION 10: STABILITY AND REACTIVITY.

#### 10.1 Reactivity.

The product does not present hazards by their reactivity.

#### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

#### 10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

#### 10.4 Conditions to avoid.

Avoid any improper handling.

#### 10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

#### **10.6 Hazardous decomposition products.**

No decomposition if used for the intended uses.

### SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

#### 11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

a) acute toxicity; Not conclusive data for classification.

Acute Toxicity Estimate (ATE): Mixtures: ATE (Oral) = 13.437 mg/kg

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1Date of compilation: 5/07/2010Version 8 (replaces version 7)Revision date: 16/03/2023

Page 7 of 30 Print date: 24/03/2023

b) skin corrosion/irritation;
 Product classified:
 Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation; Product classified: Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;Product classified:Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Not conclusive data for classification.

h) STOT-single exposure; Not conclusive data for classification.

i) STOT-repeated exposure; Not conclusive data for classification.

j) aspiration hazard; Not conclusive data for classification.

### 11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health. **Other information** 

There is no information available on other adverse health effects.

### SECTION 12: ECOLOGICAL INFORMATION.

#### 12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

#### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present. No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

#### 12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

#### 12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

#### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

#### 12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

#### 12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 8 (replaces version 7) Revision date: 16/03/2023

Page 8 of 30 Print date: 24/03/2023

### **SECTION 13: DISPOSAL CONSIDERATIONS.**

#### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

### SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID. Transport documentation: Consignment note and written instructions Sea: Transport by ship: IMDG. Transport documentation: Bill of lading <u>Air</u>: Transport by plane: ICAO/IATA. Transport document: Airway bill.

14.1 UN number or ID number.

UN No: UN3082

#### 14.2 UN proper shipping name.

Description:

ADR/RID: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL), 9, PG III, (-) IMDG: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL), 9, PG III ICAO/IATA: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL), 9, PG III

#### 14.3 Transport hazard class(es).

Class(es): 9

#### **14.4 Packing group.** Packing group: III

Packing group: III

#### 14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-F

### 14.6 Special precautions for user.

Labels: 9



Hazard number: 90 ADR LQ: 5 L

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1Date of compilation: 5/07/2010Version 8 (replaces version 7)Revision date: 16/03/2023

Page 9 of 30 Print date: 24/03/2023

IMDG LQ: 5 L ICAO LQ: 30 kg B

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Proceed in accordance with point 6.

#### 14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

### **SECTION 15: REGULATORY INFORMATION.**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC) VOC content (p/p): 0 % VOC content: 0 g/l

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

#### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### **SECTION 16: OTHER INFORMATION.**

Classification codes:

Acute Tox. 4 : Acute toxicity (Oral), Category 4 Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2 Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3 Eye Dam. 1 : Serious eye damage, Category 1 Eye Irrit. 2 : Eye irritation, Category 2 Skin Irrit. 2 : Skin irritant, Category 2 Skin Sens. 1 : Skin sensitiser, Category 1

Changes regarding to the previous version:

- Modification in the values of the physical and chemical properties (SECTION 9).

## Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

/ _/////	
Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR/RID: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CEN: European Committee for Standardization.

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



 Version 1
 Date of compilation: 5/07/2010

 Version 8 (replaces version 7)
 Revision date: 16/03/2023

Page 10 of 30 Print date: 24/03/2023

- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- PPE: Personal protection equipment.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.
- IMDG: International Maritime Code for Dangerous Goods.
- RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2020/878. Regulation (EC) No 1907/2006. Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1 Date of compilation: 5/07/2010 Version 8 (replaces version 7) Revision date: 16/03/2023 Page 11 of 30 Print date: 24/03/2023

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: Product Code: ENDURECEDOR ELASTICER 1010008

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Not available.

#### 1.3 Details of the supplier of the safety data sheet.

Company:	FIXCER PRODUCTS, S.A.U.
Address:	CTRA. SANT CUGAT KM. 3
City:	CERDANYOLA DEL VALLÈS
Province:	BARCELONA
Telephone:	93 586 20 03
Fax:	93 586 10 91
E-mail:	fixcer@fixcer.com
Web:	www.fixcer.com

**1.4 Emergency telephone number:** Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. (Available 24 hours) Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. Información en español (24h/365 días). Únicamente con la finalidad de proporcionar respuesta sanitaria en caso de urgencia.

### **SECTION 2: HAZARDS IDENTIFICATION.**

#### 2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008: Acute Tox. 4 : Harmful if swallowed.
Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects. Eye Dam. 1 : Causes serious eye damage.
Skin Corr. 1A : Causes severe skin burns and eye damage.
Skin Sens. 1 : May cause an allergic skin reaction.

#### 2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008: Pictograms:



Signal Word:

Danger

Hazard statements:

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 Wash ... thoroughly after handling.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1Date of compilation: 5/07/2010Version 8 (replaces version 7)Revision date: 16/03/2023

Page 12 of 30 Print date: 24/03/2023

 P303+P361+P353
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

 P305+P351+P338
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/...

P321 Specific treatment (see ... on this label).

#### EUH statements:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

#### Contains:

benzyl alcohol

2,4,6-tris(dimethylaminomethyl)phenol

3-aminomethyl-3,5,5-trimethylcyclohexylamine

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with mphenylenebis(methylamine)

m-phenylenebis(methylamine)

Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer

#### 2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

#### 3.1 Substances.

Not Applicable.

#### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

	Name		(*)Classification - Regulation (EC) No 1272/2008	
Identifiers		Concentrate	Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 603-057- 00-5 CAS No: 100-51-6 EC No: 202-859-9 Registration No: 01- 2119492630-38-XXXX	benzyl alcohol	1 - 50 %	Acute Tox. 4, H302+H332	-
CAS No: 68609-08-5	Cyclohexanemethanamine, 5-amino-1,3,3- trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer	5 - 50 %	Eye Dam. 1, H318 - Skin Corr. 1B, H314	-
Index No: 612-067- 00-9 CAS No: 2855-13-2 EC No: 220-666-8 Registration No: 01- 2119514687-32-XXXX	3-aminomethyl-3,5,5-trimethylcyclohexylamine	5 - 25 %	Acute Tox. 4, H302 - Eye Dam. 1, H318 - Skin Corr. 1B, H314 - Skin Sens. 1, H317	Skin Sens. 1A, H317: C ≥ 0,001 % Oral: ETA = 1030 mg/kg pc (ATP 17)
CAS No: 113930-69-1 EC No: 500-302-7 Registration No: 01- 2119965162-39-XXXX	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m- phenylenebis(methylamine)	5 - 25 %	Aquatic Chronic 3, H412 - Eye Dam. 1, H318 - Skin Corr. 1B, H314 - Skin Sens. 1, H317	-

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1 Date of compilation: 5/07/2010 Version 8 (replaces version 7) Revision date: 16/03/2023 Page 13 of 30 Print date: 24/03/2023

CAS No: 1477-55-0 EC No: 216-032-5 Registration No: 01- 2119480150-50-XXXX	[2] m-phenylenebis(methylamine)	5 - 25 %	Acute Tox. 4, H302 - Skin Corr. 1A, H314 - Skin Sens. 1, H317	-
Index No: 603-069- 00-0 CAS No: 90-72-2 EC No: 202-013-9 Registration No: 01- 2119560597-27-XXXX	2,4,6-tris(dimethylaminomethyl)phenol	1 - 10 %	Acute Tox. 4, H302	-
CAS No: 71074-89-0 EC No: 275-162-0	bis[(dimethylamino)methyl]phenol	0.1 - 1 %	Acute Tox. 3, H311	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet. [2] Substance with a national workplace exposure limit (see section 8.1).

#### \_\_\_\_\_

### SECTION 4: FIRST AID MEASURES.

#### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

#### Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

#### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners. The use of personal protective equipment is recommended for people providing first aid (see section 8).

#### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

Contact with eyes may cause irreversible damage.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract.

### **SECTION 5: FIREFIGHTING MEASURES.**

The product is NOT classified as flammable, in case of fire the following measures should be taken:

#### 5.1 Extinguishing media.

#### Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

#### Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1 Date of compilation: 5/07/2010 Version 8 (replaces version 7) Revision date: 16/03/2023 Page 14 of 30 Print date: 24/03/2023

#### 5.2 Special hazards arising from the substance or mixture.

#### Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur: - NOx (nitrogen oxides).

### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

#### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

### SECTION 6: ACCIDENTAL RELEASE MEASURES.

#### 6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

#### 6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

#### 6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

#### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

### SECTION 7: HANDLING AND STORAGE.

#### 7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

#### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and wellventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

**7.3 Specific end use(s).** Not available

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 8 (replaces version 7) Revision date: 16/03/2023

Page 15 of 30 Print date: 24/03/2023

#### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
m-phenylenebis(methylamine)	1477-55-0	Éire [1]	Eight hours		0,1
			Short term		

[1] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
benzyl alcohol	DNEL	Inhalation, Chronic, Systemic effects	90
CAS No: 100-51-6	(Workers)		(mg/m <sup>3</sup> )
EC No: 202-859-9			
2,4,6-tris(dimethylaminomethyl)phenol	DNEL	Inhalation, Chronic, Systemic effects	0,31
CAS No: 90-72-2	(Workers)		(mg/m <sup>3</sup> )
EC No: 202-013-9	. ,		

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated. DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

#### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Breathing protection:         PPE:       Filter mask for protection against gases and particles.         Characteristics:       «CE» marking, category III. The mask must have a wide field of vision and an antomically designed form in order to be sealed and watertight.         CEN standards:       EN 136, EN 140, EN 405         Maintenance:       Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1+P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.         Hand protection:       Protective gloves against chemicals.         CEN standards:       EN 374-1, En 374-2, EN 374-3, EN 420         Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.         Observations:       Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.         Material:       PVC (polyvinyl chloride)       Breakthrough time (min.):       > 480       Material thickness (mm):       0,35         Eve protection:       Protective goggles with built-in frame.       «CE» marking, category III. Eve protector with	Concentration:	100 %
PPE:       Filter mask for protection against gases and particles.         «CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.       Image: CEN standards:         CEN standards:       EN 136, EN 140, EN 405       Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.         Filter Type needed:       AZ <b>Hand protection:</b> Protective gloves against chemicals.         CEN standards:       EN 374-1, EN 374-2, EN 374-3, EN 420         Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.         Observations:       Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.         Material:       PVC (polyvinyl chloride)       Breakthrough time (min.):       A80       Material thickness (mm):       0,35         Eye protection:       Protective goggles with built-in frame.       «CE» marking, category III. Eye protector with built-in frame for protec	Uses:	
Characteristics:       «CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.       Image: CEN standards:         CEN standards:       EN 136, EN 140, EN 405         Maintenance:       Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.         Filter Type needed:       A2         Hand protection:       Protective gloves against chemicals.         CEN standards:       EN 374-1, En 374-2, EN 374-3, EN 420         Maintenance:       Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.         Observations:       Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.         Material:       PVC (polyvinyl chloride)       Breakthrough time (min.): > 480       Material thickness (mm): 0,35         Eve protection:       Protective goggles with built-in frame.       «CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.       Material thickness (mm): 0,35         Eve protection: </td <td><b>Breathing protect</b></td> <td>ction:</td>	<b>Breathing protect</b>	ction:
Characteristics:       anatomically designed form in order to be sealed and watertight.         CEN standards:       EN 136, EN 140, EN 405         Maintenance:       Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.         Filter Type needed:       A2         Hand protection:       Protective gloves against chemicals.         PPE:       Protective gloves against chemicals.         Characteristics:       «CE» marking, category III.         CEN standards:       EN 374-1, En 374-2, EN 374-3, EN 420         Maintenance:       Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.         Observations:       Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.         Material:       PVC (polyvinyl chloride)       Breakthrough time (min.): > 480       Material thickness (nm): 0,35         Eye protection:       Protective goggles with built-in frame.       «CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.       EN 165, EN	PPE:	Filter mask for protection against gases and particles.
Maintenance:       Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.         Filter Type needed:       A2         Hand protection:       Protective gloves against chemicals.         CEN standards:       EN 374-1, En 374-2, EN 374-3, EN 420         Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.         Observations:       PVC (polyvinyl chloride)         Breakthrough time (min.):       > 480         Material thickness (ms), cdaegory III.       0,35         Eye protection:       Breakthrough time (min.):       > 480         Material thickness (ms), category III.       0,35         Eye protection:       Breakthrough time (min.):       > 480         Material thickness (ms), category III.       0,35         CEs marking, category III.       Eye protector with built-in frame.       0,35         Eye protection:       Breakthrough time (min.):       > 480       Material thickness (ms).	Characteristics:	
Maintenance:       attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.         Filter Type needed:       A2         Hand protection:       Protective gloves against chemicals.         CAracteristics:       «CE» marking, category III.         CEN standards:       EN 374-1, En 374-2, EN 374-3, EN 420         Maintenance:       Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.         Observations:       Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.         Material:       PVC (polyvinyl chloride)       Breakthrough time (min.):       > 480       Material thickness (mm):       0,35         Eye protection:       Protective goggles with built-in frame.       «CE» marking, category III. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.       CEN standards:       EN 165, EN 166, EN 167, EN 168         Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.       Some signs of wear and tear include: yellow colouring of the lenses, scraping etc.    <	CEN standards:	EN 136, EN 140, EN 405
Observations:       the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.         Filter Type needed:       A2         Hand protection:       PPE:         PPE:       Protective gloves against chemicals.         Caracteristics:       «CE» marking, category III.         Maintenance:       Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.         Observations:       Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.         Material:       PVC (polyvinyl chloride)       Breakthrough time (min.):       A80       Material thickness (mm):       0,35         Eye protection:       Protective goggles with built-in frame.       CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.       Protective should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.       Observations.       Some signs of wear and tear include: yellow colouring of the lenses, scraping etc.	Maintenance:	attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.
Hand protection:         PPE:       Protective gloves against chemicals.         Characteristics:       «CE» marking, category III.         CEN standards:       EN 374-1, En 374-2, EN 374-3, EN 420         Maintenance:       Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.         Observations:       Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.         Material:       PVC (polyvinyl chloride)       Breakthrough time (min.):       0,35         Eye protection:       Protective goggles with built-in frame.       «CE» marking, category III. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.       QLS         CEN standards:       EN 165, EN 166, EN 167, EN 168       Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.         Observations:       Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.	Observations:	the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols:
PPE:       Protective gloves against chemicals.         Characteristics:       «CE» marking, category III.         CEN standards:       EN 374-1, En 374-2, EN 374-3, EN 420         Maintenance:       Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.         Observations:       Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight.         Material:       PVC (polyvinyl chloride)       Breakthrough time (min.):       0,35         Eye protection:       Protective goggles with built-in frame.       0,35         CEN standards:       Protective goggles with built-in frame.       Image: CE> marking, category III. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.         CEN standards:       EN 165, EN 166, EN 167, EN 168       Image: CE> marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.       Image: CE> marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.         CEN standards:       EN 165, EN 166, EN 167, EN 168       Image: CE> marking, category II following the manufacturer's instructions.         Observations:       Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.	Filter Type needed	: A2
Characteristics:       «CE» marking, category III.         CEN standards:       EN 374-1, En 374-2, EN 374-3, EN 420         Maintenance:       Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.         Observations:       Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight.         Always use with clean, dry hands.       Breakthrough time (min.):       > 480       Material thickness (mm):       0,35         Eye protection:       PVC (polyvinyl chloride)       Breakthrough time (min.):       > 480       Material thickness (mm):       0,35         Eye protection:       Protective goggles with built-in frame.       «CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.       Image: CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.         CEN standards:       EN 165, EN 166, EN 167, EN 168       Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.         Observations:       Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.	Hand protection	
CEN standards:       EN 374-1, En 374-2, EN 374-3, EN 420         Maintenance:       Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.         Observations:       Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.         Material:       PVC (polyvinyl chloride)       Breakthrough time (min.):       > 480       Material thickness (mm):       0,35         Eye protection:       Protective goggles with built-in frame.       «CEN marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.       Image: Should be clean. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.         Observations:       Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.	PPE:	Protective gloves against chemicals.
Maintenance:       Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.         Observations:       Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.         Material:       PVC (polyvinyl chloride)       Breakthrough time (min.):       Material thickness (mm):       0,35         Eye protection:       Protective goggles with built-in frame.       0,35       CE* marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.       CEN standards:       EN 165, EN 166, EN 167, EN 168         Maintenance:       Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.       Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.	Characteristics:	«CE» marking, category III.
Maintenance:       Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.         Observations:       Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.         Material:       PVC (polyvinyl chloride)       Breakthrough time (min.):       > 480       Material thickness (mm):       0,35         Eye protection:       Protective goggles with built-in frame.       «CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.       Image: CEs marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.       Image: CEs marking category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.       Image: CEs marking category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.         CEN standards:       EN 165, EN 166, EN 167, EN 168       Image: Should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.       Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.	CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420
Observations:       Always use with clean, dry hands.         Material:       PVC (polyvinyl chloride)       Breakthrough time (min.):       > 480       Material thickness (mm):       0,35         Eye protection:       Protective goggles with built-in frame.       «CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.       Forefore, for and vapour.       CEN standards:       EN 165, EN 166, EN 167, EN 168       Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.       Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.	Maintenance:	Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.
Material:       PVC (polyvinyl chloride)       (min.):       > 480       (mm):       0,35         Eye protection:       PPE:       Protective goggles with built-in frame.       (CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.       (CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.         CEN standards:       EN 165, EN 166, EN 167, EN 168       Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.       Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.	Observations:	
PPE:       Protective goggles with built-in frame.         Characteristics:       «CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.         CEN standards:       EN 165, EN 166, EN 167, EN 168         Maintenance:       Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.         Observations:       Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.	Material:	PV(C(polyyinyl chloride)) (135)
Characteristics:       «CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.         CEN standards:       EN 165, EN 166, EN 167, EN 168         Maintenance:       Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.         Observations:       Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.	Eye protection:	
Characteristics:       dust, smoke, fog and vapour.         CEN standards:       EN 165, EN 166, EN 167, EN 168         Maintenance:       Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.         Observations:       Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.	PPE:	Protective goggles with built-in frame.
Maintenance:Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.	Characteristics:	
Maintenance.       be disinfected periodically following the manufacturer's instructions.         Observations:       Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.	CEN standards:	EN 165, EN 166, EN 167, EN 168
Observations: scraping etc.	Maintenance:	
Skin protection:	Observations:	
	Skin protection:	

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Date of compilation: 5/07/2010 Version 1 Version 8 (replaces version 7) Revision date: 16/03/2023

Page 16 of 30 Print date: 24/03/2023

PPE:	Chemical protective clothing
	«CE» marking, category III. Clothing should fit properly. The level of protection
Characteristics:	must be set according to a test parameter called BT (Breakthrough Time), which
	indicates how long it takes for the chemical to pass through the material.
CEN standards:	EN 464,EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034
Maintonanaa	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by
Maintenance:	the manufacturer.
	The protective clothing's design should facilitate correct positioning, staying in place without moving for
Observations:	the period of use expected, bearing in mind environmental factors as well as any movement or position
	the user might adopt while carrying out the activity.
PPE:	Anti-static safety footwear against chemicals.
Characteristics:	«CE» marking, category III. Check the list of chemicals against which the footwear
Characteristics:	is resistant.
CEN standards:	EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO 20345
	For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions
Maintenance:	specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is
	observed.
Ohaanstianaa	The footwear should be cleaned regularly and dried when damp, although it should not be placed too
Observations:	close to a source of heat in order to avoid any sharp changes in temperature.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

#### 9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: Not applicable/Not available due to the nature/properties of the product Odour: Not applicable/Not available due to the nature/properties of the product Odour threshold: Not applicable/Not available due to the nature/properties of the product Melting point: Not applicable/Not available due to the nature/properties of the product Freezing point: Not applicable/Not available due to the nature/properties of the product Boiling point or initial boiling point and boiling range: Not applicable/Not available due to the nature/properties of the product Flammability: Not applicable/Not available due to the nature/properties of the product Lower explosion limit: Not applicable/Not available due to the nature/properties of the product Upper explosion limit: Not applicable/Not available due to the nature/properties of the product Flash point: > 60 °C Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product Decomposition temperature: Not applicable/Not available due to the nature/properties of the product pH: Not applicable/Not available due to the nature/properties of the product Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product Solubility: Not applicable/Not available due to the nature/properties of the product Hydrosolubility: Not applicable/Not available due to the nature/properties of the product Liposolubility: Not applicable/Not available due to the nature/properties of the product Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product Vapour pressure: Not applicable/Not available due to the nature/properties of the product Absolute density: Not applicable/Not available due to the nature/properties of the product Relative density: Not applicable/Not available due to the nature/properties of the product Relative vapour density: Not applicable/Not available due to the nature/properties of the product Particle characteristics: Not applicable/Not available due to the nature/properties of the product

#### 9.2 Other information

Not applicable/Not available due to the nature/properties of the product

### SECTION 10: STABILITY AND REACTIVITY.

#### 10.1 Reactivity.

The product does not present hazards by their reactivity.

#### 10.2 Chemical stability.

Unstable in contact with:

- Acids.
- Bases.
- Oxidizing agents.

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 8 (replaces version 7) Revision date: 16/03/2023

Page 17 of 30 Print date: 24/03/2023

#### 10.3 Possibility of hazardous reactions.

In certain conditions this may cause a polymerization reaction.

#### 10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.
- Contact with incompatible materials.

#### 10.5 Incompatible materials.

Avoid the following materials:

- Acids.
- Bases.
- Oxidizing agents.

#### 10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- COx (carbon oxides).
- Organic compounds.
- Aromatics compounds.

### SECTION 11: TOXICOLOGICAL INFORMATION.

#### 11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.

There are no tested data available on the product. Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity; Product classified: Acute toxicity (Oral), Category 4: Harmful if swallowed.

Acute Toxicity Estimate (ATE): Mixtures: ATE (Dermal) = 40.000 mg/kg ATE (Oral) = 832 mg/kg

b) skin corrosion/irritation;Product classified:Skin Corrosive, Category 1A: Causes severe skin burns and eye damage.

c) serious eye damage/irritation; Product classified: Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation; Product classified: Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Not conclusive data for classification.

h) STOT-single exposure; Not conclusive data for classification.

i) STOT-repeated exposure; Not conclusive data for classification.

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 8 (replaces version 7) Revision date: 16/03/2023

Page 18 of 30 Print date: 24/03/2023

j) aspiration hazard;Not conclusive data for classification.

### **11.2 Information on other hazards.**

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

#### Other information

There is no information available on other adverse health effects.

### SECTION 12: ECOLOGICAL INFORMATION.

#### 12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

#### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present. No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

#### 12.3 Bioaccumulative potential.

#### Information about the bioaccumulation of the substances present.

Name		Bioaccumulation			
Name	Log Pow	BCF	NOECs	Level	
benzyl alcohol	1,05	_	_	Very low	
CAS No: 100-51-6 EC No: 202-859-9	1,05	-	-	veryiow	

#### 12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

#### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

#### 12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

#### 12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

### SECTION 13: DISPOSAL CONSIDERATIONS.

#### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

### **SECTION 14: TRANSPORT INFORMATION.**

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1Date of compilation: 5/07/2010Version 8 (replaces version 7)Revision date: 16/03/2023

Page 19 of 30 Print date: 24/03/2023

Transport documentation: Consignment note and written instructions <u>Sea</u>: Transport by ship: IMDG. Transport documentation: Bill of lading <u>Air</u>: Transport by plane: ICAO/IATA. Transport document: Airway bill.

#### 14.1 UN number or ID number.

UN No: UN2735

#### 14.2 UN proper shipping name.

Description:

ADR/RID: UN 2735, AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS CYCLOHEXANEMETHANAMINE, 5-AMINO-1,3,3-TRIMETHYL-, REACTION PRODUCTS WITH BISPHENOL A DIGLYCIDYL ETHER HOMOPOLYMER / 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE), 8, PG III, (E)

IMDG: UN 2735, AMINES, LIQUID, CORRÒSIVE, N.O.S. (CONTAINS CYCLOHEXANEMETHANAMINE, 5-AMINO-1,3,3-TRIMETHYL-, REACTION PRODUCTS WITH BISPHENOL A DIGLYCIDYL ETHER HOMOPOLYMER / 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE), 8, PG III

ICAO/IATA: UN 2735, AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS CYCLOHEXANEMETHANAMINE, 5-AMINO-1,3,3-TRIMETHYL-, REACTION PRODUCTS WITH BISPHENOL A DIGLYCIDYL ETHER HOMOPOLYMER / 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE), 8, PG III

#### 14.3 Transport hazard class(es).

Class(es): 8

14.4 Packing group.

Packing group: III

#### 14.5 Environmental hazards.

Marine pollutant: No Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-B

### 14.6 Special precautions for user.

Labels: 8



Hazard number: 80 ADR LQ: 5 L IMDG LQ: 5 L ICAO LQ: 1 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Proceed in accordance with point 6. IMDG Code segregation group: 18 Alkalis

#### 14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

### SECTION 15: REGULATORY INFORMATION.

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC) VOC content (p/p): 54,125 % VOC content: 548,898 g/l

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1 Date of compilation: 5/07/2010 Version 8 (replaces version 7) Revision date: 16/03/2023 Page 20 of 30 Print date: 24/03/2023

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

#### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### **SECTION 16: OTHER INFORMATION.**

Complete text of the H phrases that appear in section 3:

H302	Harmful if swallowed.
H302+H332	Harmful if swallowed or if inhaled.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H412	Harmful to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 3 : Acute toxicity (Dermal), Category 3 Acute Tox. 4 : Acute toxicity (Inhalation), Category 4 Acute Tox. 4 : Acute toxicity (Oral), Category 4 Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2 Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3 Eye Dam. 1 : Serious eye damage, Category 1 Eye Irrit. 2 : Eye irritation, Category 2 STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3 Skin Corr. 1A : Skin Corrosive, Category 1A Skin Corr. 1B : Skin Corrosive, Category 1B Skin Irrit. 2 : Skin irritant, Category 2 Skin Sens. 1 : Skin sensitiser, Category 1 Skin Sens. 1A : Skin sensitiser, Category 1A

Changes regarding to the previous version:

- Change in the emergency number (SECTION 1.4).
- Modification of specific hazards (SECTION 2.3).
- Changes in the composition of the product (SÉCTION 3.2).
- Changes in the composition of the product (SECTION 3.2).
- Modification in the firefighting measures (SECTION 5.2).
- Modifications in the accidental release measures (SECTION 6.1).
- Modifications in the accidental release measures (SECTION 6.2).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Change in the hazard classification (SECTION 11.1).
- Modification of the classification ADR/IMDG/ICAO/IATA/RID (SECTION 14).
- Elimination of abbreviations and acronyms (SECTION 16).
- Addition of abbreviations and acronyms (SECTION 16).

## Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data Health hazards Calculation method Environmental hazards Calculation method

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Date of compilation: 5/07/2010 Version 1 Version 8 (replaces version 7)

Revision date: 16/03/2023

Page 21 of 30 Print date: 24/03/2023

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR/RID: European Agreement concerning the International Carriage of Dangerous Goods by Road.

BCF: Bioconcentration factor.

- CEN: European Committee for Standardization.
- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- EC50: Half maximal effective concentration.
- PPE: Personal protection equipment.
- International Air Transport Association. TATA:
- ICAO: International Civil Aviation Organization.
- IMDG: International Maritime Code for Dangerous Goods.
- LC50: Lethal concentration, 50%.
- LD50: Lethal dose, 50%.
- No observed effect concentration. NOEC:
- Regulations Concerning the International Transport of Dangerous Goods by Rail. RID:

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2020/878. Regulation (EC) No 1907/2006. Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1 Date of compilation: 5/07/2010 Version 8 (replaces version 7) Revision date: 16/03/2023 Page 22 of 30 Print date: 24/03/2023

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: POLVO ELASTICER Product Code: 10100PE

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Not available.

1.3 Details of the supplier of the safety data sheet.

Company:	FIXCER PRODUCTS, S.A.U.
Address:	CTRA. SANT CUGAT KM. 3
City:	CERDANYOLA DEL VALLÈS
Province:	BARCELONA
Telephone:	93 586 20 03
Fax:	93 586 10 91
Fax:	93 586 10 91
E-mail:	fixcer@fixcer.com
Web:	www.fixcer.com

**1.4 Emergency telephone number:** Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. (Available 24 hours)

Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. Información en español (24h/365 días). Únicamente con la finalidad de proporcionar respuesta sanitaria en caso de urgencia.

### **SECTION 2: HAZARDS IDENTIFICATION.**

#### 2.1 Classification of the substance or mixture.

The product is not classified as hazardous within the meaning of Regulation (EC) No 1272/2008.

#### 2.2 Label elements.

EUH statements:

EUH210Safety data sheet available on request.EUH212Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

#### 2.3 Other hazards.

The mixture does not contain substances classified as PBT. The mixture does not contain substances classified as vPvB. The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

#### 3.1 Substances.

Not Applicable.

#### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification No 127	• • • •
Identifiers	Name	Concentrate	Classification	Specifics concentration limits and Acute toxicity estimate

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 8 (replaces version 7) Revision date: 16/03/2023

Page 23 of 30 Print date: 24/03/2023

CAS No: 14808-60-7 EC No: 238-878-4	[2] Quartz (SiO2)	75 - 100 %	-	-
CAS No: 13463-67-7 EC No: 236-675-5 Registration No: 01- 2119489379-17-XXXX	[2] Titanium dioxide	2.5 - 10 %	-	-
(*) The complete text of t	the H phrases is given in section 16 of this Safety Da	ita Sheet		

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Shed

[2] Substance with a national workplace exposure limit (see section 8.1).

### SECTION 4: FIRST AID MEASURES.

#### 4.1 Description of first aid measures.

Due to the composition and type of the substances present in the product, no particular warnings are necessary.

#### Inhalation.

If breathing stops, give artificial respiration and seek immediate medical attention. Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

#### Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

#### Skin contact.

Remove contaminated clothing.

#### Ingestion.

Keep calm. NEVER induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed.

No known acute or delayed effects from exposure to the product.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

### SECTION 5: FIREFIGHTING MEASURES.

#### 5.1 Extinguishing media.

#### Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

#### Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

#### 5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

#### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account.

#### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 8 (replaces version 7) Revision date: 16/03/2023

Page 24 of 30 Print date: 24/03/2023

### SECTION 6: ACCIDENTAL RELEASE MEASURES.

#### 6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

#### 6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

#### 6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

#### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

### SECTION 7: HANDLING AND STORAGE.

#### 7.1 Precautions for safe handling.

The product does not require special handling measures, the following general measures are recommended:

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

#### 7.2 Conditions for safe storage, including any incompatibilities.

The product does not require special storage measures. As general storage measures, sources of heat, radiation, electricity and contact with food should be avoided.

Keep away from oxidising agents and from highly acidic or alkaline materials.

Store the containers between 5 and 25 ° C, in a dry and well-ventilated place.

Store according to local legislation. Observe indications on the label. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

#### 7.3 Specific end use(s).

Not available.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

#### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
		Éiro [1]	Eight hours		0,1
	14808-60-7	Éire [1]	Short term		
Quartz (SiO2)		[2] (Cal/OSHA)	Eight hours		0.05 respirable dust, 0.3 (Total Dust)
			Short term		

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1 Date of compilation: 5/07/2010 Version 8 (replaces version 7) Revision date: 16/03/2023

Page 25 of 30 Print date: 24/03/2023

		United States [3] (NIOSH)	Eight hours	Potential occupational carcinogens 0.05 respirable dust, lowest feasible concentration (LFC).
			Short term	
	United States [4] (OSHA)	Eight hours	(Total Dust) 30 mg/m3/(%SiO2 +2)	
			Short term	
		Econica [E]	Eight hours	10
		España [5]	Short term	
		United Kingdom [6]	Eight hours	10 (total inhalable)
Titanium dioxide	13463-67-7		Short term	
		Éire [1]	Eight hours	10 (Inhalable dust) 4 (Respirable dust)
			Short term	

[1] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

[2] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[3] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health,

Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[4] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[5] Según la lista de Valores Límite Ambientales de Exposición Profesional adoptados por el Instituto Nacional de Seguridad y

Salud en el Trabajo (INSST) para el año 2022. [6] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive. The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
Titanium dioxide CAS No: 13463-67-7 EC No: 236-675-5	DNEL (Workers)	Inhalation, Chronic, Local effects	10 (mg/m³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated. DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

#### 8.2 Exposure controls.

### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %	
Uses:		
Breathing protection:		
PPE:	Particle filter mask	
Characteristics:	«CE» marking, category III. Made of filtering material, it covers nose, mouth and chin.	
CEN standards:	EN 149	
Maintenance:	Check for any tears, defects, etc. before use. Since it is disposable individual protection equipment, it should be replaced after use.	
Observations:	Does not protect worker unless properly adjusted. Follow the manufacturer's instructions regarding suitable use of the equipment.	
Filter Type needed:	P2	
Hand protection:		
PPE:	Protective gloves.	

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1Date of compilation: 5/07/2010Version 8 (replaces version 7)Revision date: 16/03/2023

Page 26 of 30 Print date: 24/03/2023

Characteristics:	«CE» marking, category II.
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.
Material:	PVC (polyvinyl chloride)     Breakthrough time (min.):     > 480     Material thickness (mm):     0,35
Eye protection:	
PPE:	Protective goggles against particle impacts.
Characteristics:	«CE» marking, category II. Eye protector against dust and smoke.
CEN standards:	EN 165, EN 166, EN 167, EN 168
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.
Skin protection:	
PPE:	Protective clothing.
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.
CEN standards:	EN 340
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.
PPE:	Work footwear.
Characteristics:	«CE» marking, category II.
CEN standards:	EN ISO 13287, EN 20347
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.**

#### 9.1 Information on basic physical and chemical properties.

Physical state: Solid - Dust Colour: Not applicable/Not available due to the nature/properties of the product Odour: Not applicable/Not available due to the nature/properties of the product Odour threshold: Not available Melting point: Not available Freezing point: Not available Boiling point or initial boiling point and boiling range: Not available Flammability: Not available Lower explosion limit: Not available Upper explosion limit: Not available Flash point: Not available Auto-ignition temperature: Not available Decomposition temperature: Not available pH: Not available (Substance/mixture is non-soluble (in water)). Kinematic viscosity: Not available Solubility: Not available Hydrosolubility: Not available Liposolubility: Not available Partition coefficient n-octanol/water (log value): Not available Vapour pressure: Not available Absolute density: Not available

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1Date of compilation: 5/07/2010Version 8 (replaces version 7)Revision date: 16/03/2023

Page 27 of 30 Print date: 24/03/2023

Relative density: Not available Relative vapour density: Not available Particle characteristics: Not available

#### 9.2 Other information

Other safety characteristics Viscosity: Not available Dropping point: Not available Blink: Not available

### SECTION 10: STABILITY AND REACTIVITY.

#### 10.1 Reactivity.

The product does not present hazards by their reactivity.

#### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

#### 10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

#### 10.4 Conditions to avoid.

Avoid any improper handling.

#### 10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

#### 10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

### SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.

There are no tested data available on the product.

a) acute toxicity; Not conclusive data for classification.

b) skin corrosion/irritation; Not conclusive data for classification.

c) serious eye damage/irritation; Not conclusive data for classification.

d) respiratory or skin sensitisation; Not conclusive data for classification.

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Not conclusive data for classification.

h) STOT-single exposure; Not conclusive data for classification.

i) STOT-repeated exposure; Not conclusive data for classification.

(in accordance with Regulation (EU) 2020/878)

## ELASTICER



Version 1 Date of compilation: 5/07/2010

Version 8 (replaces version 7) Revision date: 16/03/2023

Page 28 of 30 Print date: 24/03/2023

j) aspiration hazard; Not conclusive data for classification.

### 11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

#### Other information

There is no information available on other adverse health effects.

### SECTION 12: ECOLOGICAL INFORMATION.

#### 12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

#### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present. No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

#### 12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

#### 12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

#### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

#### **12.6 Endocrine disrupting properties.**

This product doesn't contain components with environmental endocrine disrupting properties.

#### 12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

### SECTION 13: DISPOSAL CONSIDERATIONS.

#### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

### SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

(in accordance with Regulation (EU) 2020/878)

## **ELASTICER**



Version 1Date of compilation: 5/07/2010Version 8 (replaces version 7)Revision date: 16/03/2023

Page 29 of 30 Print date: 24/03/2023

#### 14.1 UN number or ID number.

Transportation is not dangerous.

#### 14.2 UN proper shipping name.

Description: ADR/RID: Not classified as hazardous for transport. IMDG: Not classified as hazardous for transport. ICAO/IATA: Not classified as hazardous for transport.

#### 14.3 Transport hazard class(es).

Transportation is not dangerous.

#### 14.4 Packing group.

Transportation is not dangerous.

#### 14.5 Environmental hazards.

Transportation is not dangerous. Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): Not applicable.

14.6 Special precautions for user.

Transportation is not dangerous.

#### 14.7 Maritime transport in bulk according to IMO instruments.

Transportation is not dangerous.

### SECTION 15: REGULATORY INFORMATION.

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

#### Volatile organic compound (VOC)

Product Subcategory (Directive 2004/42/EC): E - Special finishes (All types) Phase I\* (from 01/01/2007): 840 g/l Phase II\* (from 01/01/2010): 840 g/l (\*) g/l ready to use

VOC content (p/p): 0 % VOC content: 0 g/l

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

#### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### **SECTION 16: OTHER INFORMATION.**

Changes regarding to the previous version:

- Change in the emergency number (SECTION 1.4).

- Modification in the values of the physical and chemical properties (SECTION 9).

(in accordance with Regulation (EU) 2020/878)

## **ELASTICER**



Version 1Date of compilation: 5/07/2010Version 8 (replaces version 7)Revision date: 16/03/2023

Page 30 of 30 Print date: 24/03/2023

## Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards Health hazards Environmental hazards

On basis of test data Calculation method Calculation method

It is recommended that the product only be employed for the purposes advised.

Abbreviations and acronyms used:

- CEN: European Committee for Standardization.
- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- PPE: Personal protection equipment.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2020/878. Regulation (EC) No 1907/2006. Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.