(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



 Version 1
 Date of compilation: 21/03/2012

 Version 5 (replaces version 4)
 Revision date: 05/01/2023

Page 1 of 25 Print date: 24/03/2023

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

### 1.1 Product identifier.

Product Name: Product Code: EPOXICOLOR Comp. A EC-compA

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Not available.

### **1.3 Details of the supplier of the safety data sheet.**

Company:	FIXCER PRODUCTS, S.A.U.
Address:	CTRA. SANT CUGAT KM. 3
City:	CERDANYOLA DEL VALLÈS
Province:	BARCELONA
Telephone:	93 586 20 03
Fax:	93 586 10 91
E-mail:	fixcer@fixcer.com
Web:	www.fixcer.com

**1.4 Emergency telephone number:** Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. (Available 24 hours) Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. Información en español (24h/365 días). Únicamente con la finalidad de proporcionar respuesta sanitaria en caso de urgencia.

### **SECTION 2: HAZARDS IDENTIFICATION.**

### 2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008: Acute Tox. 4 : Harmful if swallowed. Aquatic Chronic 2 : Toxic to aquatic life with long lasting effects. Eye Dam. 1 : Causes serious eye damage. Skin Corr. 1B : Causes severe skin burns and eye damage. Skin Sens. 1 : May cause an allergic skin reaction.

### 2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008: Pictograms:



Signal Word:

Danger

Hazard statements:

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 Wash ... thoroughly after handling.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1Date of compilation: 21/03/2012Version 5 (replaces version 4)Revision date: 05/01/2023

Page 2 of 25 Print date: 24/03/2023

 P303+P361+P353
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

 P305+P351+P338
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/...

P321 Specific treatment (see ... on this label).

### EUH statements:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

### Contains:

benzyl alcohol

3-aminomethyl-3,5,5-trimethylcyclohexylamine 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with mphenylenebis(methylamine)

### 2.3 Other hazards.

The mixture does not contain substances classified as PBT. The mixture does not contain substances classified as vPvB. The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

### 3.1 Substances.

Not Applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name	Concentrate	Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 603-057- 00-5 CAS No: 100-51-6 EC No: 202-859-9 Registration No: 01- 2119492630-38-XXXX	benzyl alcohol	1 - 50 %	Acute Tox. 4, H302+H332	-
CAS No: 113930-69-1 EC No: 500-302-7 Registration No: 01- 2119965162-39-XXXX	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m- phenylenebis(methylamine)	25 - 50 %	Aquatic Chronic 2, H411 - Eye Dam. 1, H318 - Skin Corr. 1B, H314 - Skin Sens. 1, H317	-
Index No: 612-067- 00-9 CAS No: 2855-13-2 EC No: 220-666-8 Registration No: 01- 2119514687-32-XXXX	3-aminomethyl-3,5,5-trimethylcyclohexylamine	5 - 50 %	Acute Tox. 4, H302 - Eye Dam. 1, H318 - Skin Corr. 1B, H314 - Skin Sens. 1, H317	Skin Sens. 1A, H317: C ≥ 0,001 % Oral: ETA = 1030 mg/kg pc (ATP 17)

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

### **SECTION 4: FIRST AID MEASURES.**

4.1 Description of first aid measures.

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



### Version 1 Date of compilation: 21/03/2012

Version 5 (replaces version 4) Revision date: 05/01/2023

Page 3 of 25 Print date: 24/03/2023

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

#### Eve contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

#### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners. The use of personal protective equipment is recommended for people providing first aid (see section 8).

#### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

Contact with eyes may cause irreversible damage.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract.

### **SECTION 5: FIREFIGHTING MEASURES.**

The product is NOT classified as flammable, in case of fire the following measures should be taken:

#### 5.1 Extinguishing media.

### Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

#### Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

### 5.2 Special hazards arising from the substance or mixture.

### Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur: - NOx (nitrogen oxides).

### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

#### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES.**

6.1 Personal precautions, protective equipment and emergency procedures.

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1 Date of compilation: 21/03/2012

Version 5 (replaces version 4) Revision date: 05/01/2023

Page 4 of 25 Print date: 24/03/2023

For exposure control and individual protection measures, see section 8.

### 6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

### 6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

### 7.1 Precautions for safe handling.

For personal protection, see section  $\overline{8}$ .

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and wellventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

		Qualifying quantity (tonnes) for the application of	
Code	Description	Lower-tier requirements	Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS - Hazardous to the Aquatic Environment in Category Chronic 2	200	500

### 7.3 Specific end use(s).

Not available.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

#### 8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values. Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
benzyl alcohol	DNEL	Inhalation, Chronic, Systemic effects	90
CAS No: 100-51-6	(Workers)		(mg/m <sup>3</sup> )
EC No: 202-859-9			

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1 Date of compila Version 5 (replaces version 4) Date of compilation: 21/03/2012

Revision date: 05/01/2023

Page 5 of 25 Print date: 24/03/2023

#### 8.2 Exposure controls.

### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %			
Uses:				
Breathing protecti	ion.			
PPE:	Filter mask for protection against gases and particles.			
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.			
CEN standards:	EN 136, EN 140, EN 405			
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach			
Observations:	the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.			
Filter Type needed:	A2			
Hand protection: PPE:	Non dispersible protective glaves against chemicals			
Characteristics:	Non-disposable protective gloves against chemicals. «CE» marking, category III. Check the list of chemicals for which the glove has been tested.			
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420			
Maintenance:	A schedule for the periodical replacement of gloves should be established in order to guarantee their replacement before pollutants permeate them. The use of contaminated gloves could be more dangerous than not using gloves, since the pollutant can gradually accumulate in the glove's material.			
Observations:	They are to be replaced whenever tears, cracks or deformations are observed or when exterior dirt could reduce their strength.			
Material:	Breakthrough time (min.):         > 480         Material thickness (mm):         0,35			
Eye protection:				
PPE: Characteristics:	Protective goggles with built-in frame. «CE» marking, category II. Eye protector with built-in frame for protection against			
CEN standards:	dust, smoke, fog and vapour. EN 165, EN 166, EN 167, EN 168			
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.			
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.			
Skin protection:				
PPE:	Chemical protective clothing			
Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which			
CEN standards:	indicates how long it takes for the chemical to pass through the material. EN 464,EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034			
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.			
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position			
	the user might adopt while carrying out the activity.			
PPE:	Anti-static safety footwear against chemicals.			
Characteristics:	«CE» marking, category III. Check the list of chemicals against which the footwear is resistant.			
CEN standards:	EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO 20345			
Maintenance:	For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is observed.			
Observations:	The footwear should be cleaned regularly and dried when damp, although it should not be placed too close to a source of heat in order to avoid any sharp changes in temperature.			

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.**

(in accordance with Regulation (EU) 2020/878)

### **EPOXICOLOR**



Version 1Date of compilation: 21/03/2012Version 5 (replaces version 4)Revision date: 05/01/2023

Page 6 of 25 Print date: 24/03/2023

### 9.1 Information on basic physical and chemical properties.

Physical state: Liquid Colour: Not applicable/Not available due to the nature/properties of the product Odour: Not applicable/Not available due to the nature/properties of the product Odour threshold: Not applicable Melting point: Not applicable Freezing point: Not applicable Boiling point or initial boiling point and boiling range: Not applicable Flammability: Not applicable Lower explosion limit: Not applicable Upper explosion limit: Not applicable Flash point: Not applicable Auto-ignition temperature: Not applicable Decomposition temperature: Not applicable pH: Not applicable (Substance/mixture is non-soluble (in water)). Kinematic viscosity: Not applicable Solubility: Not applicable Hydrosolubility: Not applicable Liposolubility: Not applicable Partition coefficient n-octanol/water (log value): Not applicable Vapour pressure: Not applicable Absolute density: Not applicable Relative density: Not applicable Relative vapour density: Not applicable Particle characteristics: Not applicable

### 9.2 Other information

Other safety characteristics Viscosity: Not applicable Dropping point: Not applicable Blink: Not applicable

### SECTION 10: STABILITY AND REACTIVITY.

### 10.1 Reactivity.

The product does not present hazards by their reactivity.

#### 10.2 Chemical stability.

Unstable in contact with:

- Acids.

- Bases.

- Oxidizing agents.

#### 10.3 Possibility of hazardous reactions.

In certain conditions this may cause a polymerization reaction.

#### 10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.
- Contact with incompatible materials.

#### 10.5 Incompatible materials.

Avoid the following materials:

- Acids.
- Bases.
- Oxidizing agents.

#### 10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- COx (carbon oxides).
- Organic compounds.
- Aromatics compounds.

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1 Date of compilation: 21/03/2012 Version 5 (replaces version 4) Revision date: 05/01/2023 Page 7 of 25 Print date: 24/03/2023

### SECTION 11: TOXICOLOGICAL INFORMATION.

### 11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.

There are no tested data available on the product. Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity; Product classified: Acute toxicity (Oral), Category 4: Harmful if swallowed.

Acute Toxicity Estimate (ATE): Mixtures: ATE (Oral) = 714 mg/kg

b) skin corrosion/irritation;Product classified:Skin Corrosive, Category 1B: Causes severe skin burns and eye damage.

c) serious eye damage/irritation; Product classified: Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;Product classified:Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Not conclusive data for classification.

h) STOT-single exposure; Not conclusive data for classification.

i) STOT-repeated exposure; Not conclusive data for classification.

j) aspiration hazard; Not conclusive data for classification.

### 11.2 Information on other hazards.

**Endocrine disrupting properties** This product does not contain components with endocrine-disrupting properties with effects on human health.

<u>Other information</u> There is no information available on other adverse health effects.

### SECTION 12: ECOLOGICAL INFORMATION.

#### 12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1 Date of compilation: 21/03/2012

Version 5 (replaces version 4) Revision date: 05/01/2023

Page 8 of 25 Print date: 24/03/2023

### 12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name		Bioaccumulation			
		Log Pow	BCF	NOECs	Level
benzyl alcohol		1,05	_	_	Very low
CAS No: 100-51-6	EC No: 202-859-9	1,05			VCI y IOW

### 12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

#### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

#### **12.6 Endocrine disrupting properties.**

This product doesn't contain components with environmental endocrine disrupting properties.

#### 12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

### SECTION 13: DISPOSAL CONSIDERATIONS.

#### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

### **SECTION 14: TRANSPORT INFORMATION.**

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1Date of compilation: 21/03/2012Version 5 (replaces version 4)Revision date: 05/01/2023

Page 9 of 25 Print date: 24/03/2023

### 14.1 UN number or ID number.

UN No: UN2735

### 14.2 UN proper shipping name.

Description:

ADR/RID: UN 2735, AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE, REACTION PRODUCTS WITH M-PHENYLENEBIS(METHYLAMINE) / 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE), 8, PG II, (E) IMDG: UN 2735, AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE, REACTION PRODUCTS WITH M-PHENYLENEBIS(METHYLAMINE) / 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE), 8, PG II, MARINE POLLUTANT ICAO/IATA: UN 2735, AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE, REACTION PRODUCTS WITH M-PHENYLENEBIS(METHYLAMINE) / 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE), 8, PG II, MARINE POLLUTANT ICAO/IATA: UN 2735, AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE, REACTION PRODUCTS WITH M-PHENYLENEBIS(METHYLAMINE) / 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE), 8, PG II

### 14.3 Transport hazard class(es).

Class(es): 8

14.4 Packing group.

Packing group: II

### 14.5 Environmental hazards.



Dangerous for the environment Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-B

### 14.6 Special precautions for user.

Labels: 8



Hazard number: 80 ADR LQ: 1 L IMDG LQ: 1 L ICAO LQ: 0,5 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Proceed in accordance with point 6. IMDG Code segregation group: 18 Alkalis

### 14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

### SECTION 15: REGULATORY INFORMATION.

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC) VOC content (p/p): 70 %

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1 Date of compilation: 21/03/2012 Version 5 (replaces version 4) Revision date: 05/01/2023 Page 10 of 25 Print date: 24/03/2023

VOC content: 722,325 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): E2

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### **SECTION 16: OTHER INFORMATION.**

Complete text of the H phrases that appear in section 3:

H302	Harmful if swallowed.
H302+H332	Harmful if swallowed or if inhaled.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 : Acute toxicity (Inhalation), Category 4 Acute Tox. 4 : Acute toxicity (Oral), Category 4 Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2 Eye Dam. 1 : Serious eye damage, Category 1 Skin Corr. 1B : Skin Corrosive, Category 1B Skin Sens. 1 : Skin sensitiser, Category 1 Skin Sens. 1A : Skin sensitiser, Category 1A

Changes regarding to the previous version:

- Change of the name of the product (SECTION 1.1).
- Change of the uses of the product (SECTION 1.2).
- Change in the emergency number (SECTION 1.4).
- Change in the hazard classification (SECTION 2.1).
- Removal of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Addition of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Modification of specific hazards (SECTION 2.3).
- Changes in the composition of the product (SECTION 3.2).
- Changes in the composition of the product (SECTION 3.2).
- Changes in the composition of the product (SECTION 3.2).
- Modification in the firefighting measures (SECTION 5.2).
- Modifications in the accidental release measures (SECTION 6.1).
- Modifications in the accidental release measures (SECTION 6.2).
- Modifications in the handling and storage precautions (SECTION 7.1).
- Modifications in the handling and storage precautions (SECTION 7.2).
- Addition of personal protective equipment (SECTION 8.2).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Change in the hazard classification (SECTION 11.1).
- Modification of the classification ADR/IMDG/ICAO/IATA/RID (SECTION 14).
- National legislative changes (SECTION 15.1).
- Elimination of abbreviations and acronyms (SECTION 16).
- Addition of abbreviations and acronyms (SECTION 16).

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1Date of compilation: 21/03/2012Version 5 (replaces version 4)Revision date: 05/01/2023

Page 11 of 25 Print date: 24/03/2023

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC)

**1272/2008 [CLP]:** Physical hazards Health hazards Environmental hazards

On basis of test data Calculation method Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR/RID: European Agreement concerning the International Carriage of Dangerous Goods by Road.

- BCF: Bioconcentration factor.
- CEN: European Committee for Standardization.
- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- EC50: Half maximal effective concentration.
- PPE: Personal protection equipment.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.
- IMDG: International Maritime Code for Dangerous Goods.
- LC50: Lethal concentration, 50%.
- LD50: Lethal dose, 50%.
- NOEC: No observed effect concentration.
- RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2020/878. Regulation (EC) No 1907/2006. Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1 Date of compilation: 21/03/2012 Version 5 (replaces version 4) Revision date: 05/01/2023 Page 12 of 25 Print date: 24/03/2023

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

### 1.1 Product identifier.

Product Name: Product Code:

EPOXICOLOR - comp. B EC-compB

### 1.2 Relevant identified uses of the substance or mixture and uses advised against.

Recubrimiento epoxi

### Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company:	FIXCER PRODUCTS, S.A.U.
Address:	CTRA. SANT CUGAT KM. 3
City:	CERDANYOLA DEL VALLÈS
Province:	BARCELONA
Telephone:	93 586 20 03
Fax:	93 586 10 91
E-mail:	fixcer@fixcer.com
Web:	www.fixcer.com

**1.4 Emergency telephone number:** Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. (Available 24 hours)

Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. Información en español (24h/365 días). Únicamente con la finalidad de proporcionar respuesta sanitaria en caso de urgencia.

### SECTION 2: HAZARDS IDENTIFICATION.

### 2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008: Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects. Eye Irrit. 2 : Causes serious eye irritation.

Skin Irrit. 2 : Causes skin irritation.

Skin Sens. 1 : May cause an allergic skin reaction.

### 2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008: Pictograms:



Signal Word:

Warning

Hazard statements:

Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Harmful to aquatic life with long lasting effects.

Precautionary statements:

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Page 13 of 25

Print date: 24/03/2023

Version 1 Date of compilation: 21/03/2012					
Version 5 (	replaces version 4)	Revision date: 05/01/2023			
53.63		, , , , , , ,			

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P262	Do not get in eyes, on skin, or on clothing.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.

EUH statements: EUH205

Contains epoxy constituents. May produce an allergic reaction.

Contains:

bis-[4-(2,3-epoxipropoxi)phenyl]propane oxirane, mono[(C12-14-alkyloxy)methyl] derivs. Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

### 2.3 Other hazards.

The mixture does not contain substances classified as PBT. The mixture does not contain substances classified as vPvB. The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

### 3.1 Substances.

Not Applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name	Concentrate	Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 603-073- 00-2 CAS No: 1675-54-3 EC No: 216-823-5	bis-[4-(2,3-epoxipropoxi)phenyl]propane	5 - 50 %	Eye Irrit. 2, H319 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	Eye Irrit. 2, H319: C ≥ 5 % Skin Irrit. 2, H315: C ≥ 5 %
CAS No: 9003-36-5 EC No: 500-006-8 Registration No: 01- 2119454392-40-XXXX	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	10 - 25 %	Aquatic Chronic 3, H412 - Eye Irrit. 2, H319 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
Index No: 603-103- 00-4 CAS No: 68609-97-2 EC No: 271-846-8 Registration No: 01- 2119485289-22-XXXX	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	10 - 25 %	Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
Index No: 601-022- 00-9 CAS No: 1330-20-7 EC No: 215-535-7 Registration No: 01- 2119488216-32-XXXX	[1] [2] xylene	0 - 10 %	-	-

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1 Date of compilation: 21/03/2012

Version 5 (replaces version 4) Revision date: 05/01/2023

Page 14 of 25 Print date: 24/03/2023

Index No: 601-023- 00-4 CAS No: 100-41-4 EC No: 202-849-4 Registration No: 01- 2119489370-35-XXXX	[1] [2] ethylbenzene	0 - 10 %	-	-
Index No: 603-108- 00-1 CAS No: 78-83-1 EC No: 201-148-0 Registration No: 01- 2119484609-23-XXXX	[2] 2-methylpropan-1-ol, iso-butanol	0 - 1 %	-	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a European Union exposure limit in the workplace (see section 8.1).

[2] Substance with a national workplace exposure limit (see section 8.1).

### **SECTION 4: FIRST AID MEASURES.**

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

### Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

#### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

### **SECTION 5: FIREFIGHTING MEASURES.**

The product is NOT classified as flammable, in case of fire the following measures should be taken:

### 5.1 Extinguishing media.

### Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

#### Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

#### 5.2 Special hazards arising from the substance or mixture.

#### Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

(in accordance with Regulation (EU) 2020/878)

### EPOXICOLOR



Date of compilation: 21/03/2012 Version 1

Version 5 (replaces version 4) Revision date: 05/01/2023

Page 15 of 25 Print date: 24/03/2023

### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

### SECTION 6: ACCIDENTAL RELEASE MEASURES.

#### 6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

### 6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

### 6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

### **SECTION 7: HANDLING AND STORAGE.**

### 7.1 Precautions for safe handling.

For personal protection, see section 8. In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and wellventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

### 7.3 Specific end use(s).

Not available.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

### 8.1 Control parameters.

Work exposure limit for:

	Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
--	------	---------	---------	-------------	-----	-------------------

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1Date of compilation: 21/03/2012Version 5 (replaces version 4)Revision date: 05/01/2023

Page 16 of 25 Print date: 24/03/2023

			Eight hours	50(vía dérmica, sensibilizante)	221(vía dérmica, sensibilizante)
		España [1]	Short term	100(vía dérmica, sensibilizante)	442(vía dérmica, sensibilizante)
		European	Eight hours	50 (skin)	221 (skin)
		Union [2]	Short term	100 (skin)	442 (skin)
	1330-20-7	United	Eight hours	50	220
xylene		Kingdom [3]	Short term	100	441
			Eight hours	50	221
		Éire [4]	Short term	100	442
		United States	Eight hours	100	112
		[5] (Cal/OSHA)	Short term	150 (Ceiling) 300	
		United States	Eight hours	100 (ceiling) 500	
		[6] (NIOSH)	Short term	150	
		United States	Eight hours	100	435
		[7] (OSHA)	Short term	100	755
			Short term		441(Vía
		España [1]	Eight hours	100(Vía dérmica)	dérmica)
			Short term	200(Vía dérmica)	884(Vía dérmica)
	100-41-4	European	Eight hours	100 (skin)	442 (skin)
		Union [2]	Short term	200 (skin)	884 (skin)
		United	Eight hours	100	441
		Kingdom [3]	Short term	125	552
ethylbenzene		Éire [4] United States [5] (Cal/OSHA)	Eight hours	100	442
			Short term	200	884
			Eight hours	5	
			Short term	30	
		United States	Eight hours	100	
		[6] (NIOSH)	Short term	125	
		United States	Eight hours	100	435
		[7] (OSHA)	Short term		
		Fama % a. [1]	Eight hours	50	154
		España [1]	Short term		
		United	Eight hours	50	154
		Kingdom [3]	Short term	75	231
		Éire [4]	Eight hours	50	150
2 mothydropop 1 ol ico bytarol	78-83-1	Eire [4]	Short term	75	225
2-methylpropan-1-ol, iso-butanol	/0-03-1	United States	Eight hours	50	
		[5] (Cal/OSHA)	Short term		
		United States	Eight hours	50	
		[6] (NIOSH)	Short term		
		United States	Eight hours	100	300
1		[7] (OSHA)	Short term		

Biological exposure limit values for:

Name	CAS No.	Country	Biological indicator	BLV	Sampling time
xylene	1330-20-7	España [1]	Ácidos metilhipúricos en orina	1 g/g creatinina	Final de la jornada laboral
ethylbenzene	100-41-4	España [1]	Suma del acido mandélico y el ácido fenilglioxílico en orina	700 mg/g creatinina	Final de la semana laboral

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1 Date of compilation: 21/03/2012

Version 5 (replaces version 4) Revision date: 05/01/2023

Page 17 of 25 Print date: 24/03/2023

[1] Según la lista de Valores Límite Ambientales de Exposición Profesional adoptados por el Instituto Nacional de Seguridad y Salud en el Trabajo (INSST) para el año 2022.

[2] According both Binding Occupational Esposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[3] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive.

[4] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

[5] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[6] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health,

Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[7] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs),

California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
ovirano mono[(C12,14, alle dove)methyd] derive	DNEL	Inhalation, Chronic, Local effects	0,98
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. CAS No: 68609-97-2	(Workers)		(mg/m <sup>3</sup> )
EC No: 271-846-8	DNEL	Inhalation, Chronic, Systemic effects	13,8
EC NO. 271-040-0	(Workers)		(mg/m <sup>3</sup> )
xylene	DNEL	Inhalation, Chronic, Systemic effects	77
CAS No: 1330-20-7	(Workers)		(mg/m <sup>3</sup> )
EC No: 215-535-7			
ethylbenzene	DNEL	Inhalation, Chronic, Systemic effects	77
CAS No: 100-41-4	(Workers)		(mg/m <sup>3</sup> )
EC No: 202-849-4			
2 mathulayanan 1 al isa hutanal	DNEL	Inhalation, Chronic, Local effects	310
2-methylpropan-1-ol, iso-butanol	(Workers)		(mg/m <sup>3</sup> )
CAS No: 78-83-1 EC No: 201-148-0	DNEL	Inhalation, Chronic, Local effects	55
EC NO. 201-140-0	(Consumers)		(mg/m <sup>3</sup> )

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated. DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum. Concentration levels PNEC:

Name	Details	Value
	aqua (freshwater)	0,4 (mg/L)
	aqua (marine water)	0,04 (mg/L)
	aqua (intermittent releases)	11 (mg/L)
	STP	10 (mg/L)
2-methylpropan-1-ol, iso-butanol	sediment (freshwater)	1,52 (mg/kg
CAS No: 78-83-1		sediment dw)
EC No: 201-148-0	sediment (marine water)	0,152 (mg/kg
		sediment dw)
	soil	0,0699
		(mg/kg soil
		dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

#### 8.2 Exposure controls.

### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	Recubrimiento epoxi
<b>Breathing protecti</b>	on:
PPE:	Filter mask for protection against gases and particles.
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.
CEN standards:	EN 136, EN 140, EN 405

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1Date of compilation: 21/03/2012Version 5 (replaces version 4)Revision date: 05/01/2023

Page 18 of 25 Print date: 24/03/2023

Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.			
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.			
Filter Type needed				
Hand protection				
PPE:	Protective gloves against chemicals.			
Characteristics:	«CE» marking, category III.			
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420			
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.			
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.			
Material:	PVC (polyvinyl chloride)     Breakthrough time (min.):     > 480     Material thickness (mm):     0,35			
Eye protection:				
PPE:	Protective goggles with built-in frame.			
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.			
CEN standards:	EN 165, EN 166, EN 167, EN 168			
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.			
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.			
Skin protection:				
PPE:	Chemical protective clothing			
Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.			
CEN standards:	EN 464,EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034			
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.			
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.			
PPE:	Work footwear.			
Characteristics:	«CE» marking, category II.			
CEN standards:	EN ISO 13287, EN 20347			
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.			
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident			

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

### 9.1 Information on basic physical and chemical properties.

Physical state: Liquid Colour: Not applicable/Not available due to the nature/properties of the product Odour: Not applicable/Not available due to the nature/properties of the product Odour threshold: Not applicable Melting point: Not applicable Freezing point: Not applicable Boiling point or initial boiling point and boiling range: Not applicable Flammability: Not applicable Lower explosion limit: Not applicable Upper explosion limit: Not applicable Flash point: Not applicable Auto-ignition temperature: Not applicable Decomposition temperature: Not applicable

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1Date of compilation: 21/03/2012Version 5 (replaces version 4)Revision date: 05/01/2023

Page 19 of 25 Print date: 24/03/2023

pH: Not applicable (Substance/mixture is non-soluble (in water)). Kinematic viscosity: Not applicable Solubility: Not applicable Hydrosolubility: Not applicable Liposolubility: Not applicable Partition coefficient n-octanol/water (log value): Not applicable Vapour pressure: Not applicable Absolute density: Not applicable Relative density: Not applicable Relative vapour density: Not applicable Particle characteristics: Not applicable

### 9.2 Other information

### Other safety characteristics

Viscosity: Not applicable Dropping point: Not applicable Blink: Not applicable

### SECTION 10: STABILITY AND REACTIVITY.

#### 10.1 Reactivity.

The product does not present hazards by their reactivity.

### 10.2 Chemical stability.

Unstable in contact with:

- Acids.
- Bases.
- Oxidizing agents.

#### 10.3 Possibility of hazardous reactions.

In certain conditions this may cause a polymerization reaction.

### 10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.
- Contact with incompatible materials.

### 10.5 Incompatible materials.

Avoid the following materials:

- Acids.
- Bases.
- Oxidizing agents.

#### 10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- COx (carbon oxides).
- Organic compounds.
- Aromatics compounds.

### SECTION 11: TOXICOLOGICAL INFORMATION.

### IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

#### 11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

#### Toxicological information about the substances present in the composition.

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1Date of compilation: 21/03/2012Version 5 (replaces version 4)Revision date: 05/01/2023

Page 20 of 25 Print date: 24/03/2023

	N		Acute toxicity			
	Name	Туре	Test	Kind	Value	
			LD50	Rat	4300 mg/kg bw [1]	
		Oral				
			[1] AMA A	rchives of Indus	trial Health. Vol. 14, Pg. 387, 1956	
xylene			LD50	Rabbit	> 1700 mg/kg bw [1]	
Ayichic		Dermal				
		Dermai			ndbook, Vol.1: Organic Solvents,	
			-	1, Pg. 123, 197		
			LC50	Rat	21,7 mg/l/4 h [1]	
		Inhalation				
CAS No: 1330-20-7	EC No: 215-535-7				dbook, Vol.1: Organic Solvents,	
				1, Pg. 123, 197		
			LD50	Rat	3500 mg/kg bw [1]	
		Oral	F47 444 4			
					trial Health. Vol. 14, Pg. 387, 1956	
ethylbenzene			LD50	Rabbit	15400 mg/kg bw [1]	
		Dermal				
			[1] Food a	ind Cosmetics To	oxicology. Vol. 13, Pg. 803, 1975	
CAS No: 100-41-4	EC No: 202-849-4	Inhalation				

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;Product classified:Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation; Product classified: Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;Product classified:Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Not conclusive data for classification.

h) STOT-single exposure; Not conclusive data for classification.

i) STOT-repeated exposure; Not conclusive data for classification.

j) aspiration hazard; Not conclusive data for classification.

### 11.2 Information on other hazards.

### Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

### Other information

There is no information available on other adverse health effects.

### SECTION 12: ECOLOGICAL INFORMATION.

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1Date of compilation: 21/03/2012Version 5 (replaces version 4)Revision date: 05/01/2023

Page 21 of 25 Print date: 24/03/2023

### 12.1 Toxicity.

Nama		Ecotoxicity					
Name	Туре	Test	Kind	Value			
	Fish	LC50 Fish 15,7 mg/l (96 h) [ [1] Bailey, H.C., D.H.W. Liu, and H.A. Javitz 1985. Time/Toxicity Relationships in Short-Term Static, Dyna and Plug-Flow Bioassays. In: R.C.Bahner and D.J.Han (Eds.), Aquatic Toxicology and Hazard Assessment, 8tl Symposium, ASTM STP 891, Philadelphia, PA :193-212					
xylene	Aquatic invertebrates	LC50 [1] Tatem, Toxicity of Crustacean H.E. 1975. Petroleum Palaemone					
CAS No: 1330-20-7 EC No: 215-535-7	Aquatic plants						
	Fish	LC50Fish80 mg/l (96 h) [1][1] Mayer, F.L.Jr., and M.R. Ellersieck 1986.Manual ofAcute Toxicity:Interpretation and Data Base for 410Chemicals and 66 Species of Freshwater Animals.Resour.Publ.No.160, U.S.Dep.Interior, Fish Wildl.Serv.,Washington, DC :505 p. (USGS Data File)					
ethylbenzene	Aquatic invertebrates	LC50 [1] MacLea Toxicity of	Crustacean n, M.M., and K.G. Do Crude and Refined C nvironment Canada,	16,2 mg/l (48 h) [1] be 1989. The Comparative bils to Daphnia magna and EE-111, Dartmouth, Nova			
CAS No: 100-41-4 EC No: 202-849-4	Aquatic plants	M.L. Tosato of Aquatic ( Ecotoxicol.I Boeri, and Determine Highly Vola	0 1988. Approaches Organisms to Aroma Environ.Saf. 16(2):19 J.D. Walker 1994. S	58-169. Masten, L.W., R.L. tategies Employed to oxicity of Ethyl Benzene, a oluble Chemical.			

### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present. No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

### 12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

	Name		Bioac	cumulation	
		Log Pow	BCF	NOECs	Level
ethylbenzene		3,15	_	-	Moderate
CAS No: 100-41-4	EC No: 202-849-4	5,15			Hoderate

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1 Date of compilation: 21/03/2012

Version 5 (replaces version 4) Revision date: 05/01/2023

Page 22 of 25 Print date: 24/03/2023

2-methylpropan-1-ol, iso-butanol		0.70			
CAS No: 78-83-1	EC No: 201-148-0	0,76	-	-	Very low

### 12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

#### 12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

### SECTION 13: DISPOSAL CONSIDERATIONS.

### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

### SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID. Transport documentation: Consignment note and written instructions Sea: Transport by ship: IMDG. Transport documentation: Bill of lading <u>Air</u>: Transport by plane: ICAO/IATA. Transport document: Airway bill.

### 14.1 UN number or ID number.

UN No: UN3082

### 14.2 UN proper shipping name.

Description:

ADR/RID: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL), 9, PG III, (-)

IMDG: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL), 9, PG III

ICAO/IATA: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL), 9, PG III

### 14.3 Transport hazard class(es).

Class(es): 9

**14.4 Packing group.** Packing group: III

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1Date of compilation: 21/03/2012Version 5 (replaces version 4)Revision date: 05/01/2023

Page 23 of 25 Print date: 24/03/2023

### 14.5 Environmental hazards.



Dangerous for the environment Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-F

### 14.6 Special precautions for user.

Labels: 9



Hazard number: 90 ADR LQ: 5 L IMDG LQ: 5 L ICAO LQ: 30 kg B

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Proceed in accordance with point 6.

### 14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

### SECTION 15: REGULATORY INFORMATION.

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC) VOC content (p/p): 0,943 % VOC content: 8,803 g/l

The product is not affected by Directive 2012/18/EU (SEVESO III). The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products. The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### **SECTION 16: OTHER INFORMATION.**

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4 Acute Tox. 4 : Acute toxicity (Inhalation), Category 4 Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2

(in accordance with Regulation (EU) 2020/878)

### **EPOXICOLOR**



Version 1Date of compilation: 21/03/2012Version 5 (replaces version 4)Revision date: 05/01/2023

Page 24 of 25 Print date: 24/03/2023

Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3 Asp. Tox. 1 : Aspiration toxicity, Category 1 Eye Dam. 1 : Serious eye damage, Category 1 Eye Irrit. 2 : Eye irritation, Category 2 Flam. Liq. 2 : Flammable liquid, Category 2 Flam. Liq. 3 : Flammable liquid, Category 3 STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2 STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3 Skin Irrit. 2 : Skin irritant, Category 2 Skin Sens. 1 : Skin sensitiser, Category 1

Changes regarding to the previous version:

- Change in the emergency number (SECTION 1.4).
- Change in the hazard classification (SECTION 2.1).
- Removal of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Addition of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Modification of specific hazards (SECTION 2.3).
- Changes in the composition of the product (SECTION 3.2).
- Changes in the composition of the product (SECTION 3.2).
- Changes in the composition of the product (SECTION 3.2).
- Modification in the firefighting measures (SECTION 5.2).
- Modifications in the accidental release measures (SECTION 6.1).
- Modifications in the accidental release measures (SECTION 6.2).
- Modifications in the handling and storage precautions (SECTION 7.1).
- Modifications in the handling and storage precautions (SECTION 7.2).
- Modification of exposure data (SECTION 8.1).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Modification of the information of the stability and reactivity conditions (SECTION 10.6).
- Change in the hazard classification (SECTION 11.1).
- Modification of the classification ADR/IMDG/ICAO/IATA/RID (SECTION 14).
- National legislative changes (SECTION 15.1).
- Elimination of abbreviations and acronyms (SECTION 16).
- Addition of abbreviations and acronyms (SECTION 16).

## Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR/RID: European Agreement concerning the International Carriage of Dangerous Goods by Road.

- BCF: Bioconcentration factor.
- CEN: European Committee for Standardization.
- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be
- considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- EC50: Half maximal effective concentration.
- PPE: Personal protection equipment.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.
- IMDG: International Maritime Code for Dangerous Goods.
- LC50: Lethal concentration, 50%.
- LD50: Lethal dose, 50%.
- NOEC: No observed effect concentration.
- PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

(in accordance with Regulation (EU) 2020/878)

## **EPOXICOLOR**



Version 1Date of compilation: 21/03/2012Version 5 (replaces version 4)Revision date: 05/01/2023

Page 25 of 25 Print date: 24/03/2023

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2020/878. Regulation (EC) No 1907/2006. Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.