(in accordance with Regulation (EU) 2020/878)

# FIXCER EUROCOLOR FLEX



Version 1 Date of compilation: 18/02/2020

Version 14 (replaces version 13) Revision date: 17/03/2023

Page 1 of 10 Print date: 24/03/2023

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: FIXCER EUROCOLOR FLEX Product Code: EUBL

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Mortero de cemento coloreado para el sellado de juntas

#### Uses advised against:

Uses other than those recommended.

#### 1.3 Details of the supplier of the safety data sheet.

Company:	FIXCER PRODUCTS, S.A.U.
Address:	CTRA. SANT CUGAT KM. 3
City:	CERDANYOLA DEL VALLÈS
Province:	BARCELONA
Telephone:	93 586 20 03
Fax:	93 586 10 91
E-mail:	fixcer@fixcer.com
Web:	www.fixcer.com

**1.4 Emergency telephone number:** Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. (Available 24 hours)

Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420. Información en español (24h/365 días). Únicamente con la finalidad de proporcionar respuesta sanitaria en caso de urgencia.

### **SECTION 2: HAZARDS IDENTIFICATION.**

#### 2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Eye Dam. 1 : Causes serious eye damage.

STOT SE 3 : May cause respiratory irritation.

Skin Irrit. 2 : Causes skin irritation. Skin Sens. 1 : May cause an allergic skin reaction.

### 2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008: Pictograms:



Signal Word:

P261

Danger Hazard statements:

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.

Precautionary statements:

Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

(in accordance with Regulation (EU) 2020/878)

# FIXCER EUROCOLOR FLEX



Version 1 Date of compilation: 18/02/2020 Version 14 (replaces version 13) Revision date: 17/03/2023 Page 2 of 10 Print date: 24/03/2023

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310Immediately call a POISON CENTER/doctor/...P321Specific treatment (see ... on this label).P403+P233Store in a well-ventilated place. Keep container tightly closed.P501Dispose of contents/container to ...

Contains: Cement, portland, chemicals

#### 2.3 Other hazards.

The mixture does not contain substances classified as PBT. The mixture does not contain substances classified as vPvB. The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

#### 3.1 Substances.

Not Applicable.

#### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
Identifiers			Classification	Specifics concentration limits and Acute toxicity estimate
CAS No: 65997-15-1 EC No: 266-043-4	[2] Cement, portland, chemicals	20 - 50 %	Eye Dam. 1, H318 - STOT SE 3, H335 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[2] Substance with a national workplace exposure limit (see section 8.1).

### **SECTION 4: FIRST AID MEASURES.**

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

#### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

#### Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

#### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

#### Ingestion.

(in accordance with Regulation (EU) 2020/878)

# FIXCER EUROCOLOR FLEX



Version 1 Date of compilation: 18/02/2020

Version 14 (replaces version 13) Revision date: 17/03/2023

Page 3 of 10 Print date: 24/03/2023

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Contact with eyes may cause irreversible damage.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

Request immediate medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

### **SECTION 5: FIREFIGHTING MEASURES.**

The product is NOT classified as flammable, in case of fire the following measures should be taken:

#### 5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

#### Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

#### 5.2 Special hazards arising from the substance or mixture.

#### Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

#### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

#### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

### SECTION 6: ACCIDENTAL RELEASE MEASURES.

#### 6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

#### 6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

#### 6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

#### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

### **SECTION 7: HANDLING AND STORAGE.**

#### 7.1 Precautions for safe handling.

For personal protection, see section 8.

(in accordance with Regulation (EU) 2020/878)

# FIXCER EUROCOLOR FLEX



Version 1 Date of compilation: 18/02/2020

Version 14 (replaces version 13) Revision date: 17/03/2023

Page 4 of 10 Print date: 24/03/2023

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

#### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

#### 8.1 Control parameters.

Work exposure limit for:

Cement, portland, chemicals 65997-15-1 España [1] Eight hours 4 (fracción respirable) (fraction)   United Kingdom [2] United Kingdom [2] Eight hours 10 (inhalable dust) 4 (respirable dust)   United States [4] (Cal/OSHA) Eight hours 1 (Respirable fraction)   United States [5] (NIOSH) Eight hours 10 (Total dust)   Short term 10 (Total dust) 5 (Respirable fraction)   Short term 10 (Total dust) 5 (Respirable fraction)   Short term 10 (Total dust) 5 (Respirable fraction)   United States [5] (NIOSH) Eight hours 10 (Total dust)   Short term 10 (Total dust) 5 (Respirable fraction)   United States [6] (NIOSH) Eight hours 5 (Respirable fraction)   United States [6] (OSHA) Eight hours 15 (Total dust)   Short term 10 (Total dust) 5 (Respirable fraction)   Short term 10 (Total dust) 5 (Respirable fraction)   Short term 10 (Total dust) 5 (Respirable fraction)   Short term 10 (Total dust) 10 (Total dust)   Stort term <th>Name</th> <th>CAS No.</th> <th>Country</th> <th>Limit value</th> <th>ppm</th> <th>mg/m<sup>3</sup></th>	Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
Cement, portland, chemicals 65997-15-1   65997-15-1   Image: Comparison of the second se			España [1]	Eight hours		
Cement, portland, chemicals 65997-15-1   Image: Signed series of the ser				Short term		
Cement, portland, chemicals 65997-15-1   Eight hours 10 (Total dust)   5 (Respirable (4) (Cal/OSHA) 10 (Total dust)   Eight hours 5 (Respirable fraction)   United States [5] (NIOSH) Eight hours 10 (Total dust)   Short term 10 (Total dust)   Short term 10 (Total dust)   United States [5] (NIOSH) Eight hours 10 (Total dust)   Short term 10 (Total dust)   United States [5] (NIOSH) Fight hours 10 (Total dust)   United States [6] (OSHA) Eight hours 15 (Total dust)   Short term 15 (Total dust) 15 (Respirable fraction)   United States [6] (OSHA) Eight hours 15 (Total dust)   Short term 15 (Total dust) 10 (mpcf:Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques, Conversion fractors - mpcf X 35.3 = million particles per cubic meter = particles per				Eight hours		dust) 4
Cement, portland, chemicals 65997-15-1   Eight hours 10 (Total dust) 5 (Respirable fraction)   United States [5] (NIOSH) Eight hours   Bort term 10 (Total dust) 5 (Respirable fraction)   Short term 10 (Total dust) 5 (Respirable fraction)   Short term 10 (Total dust) 5 (Respirable fraction)   United States [5] (NIOSH) Eight hours   United States [6] (OSHA) Eight hours   Eight hours 15 (Total dust) 5 (Respirable fraction) 50 (mppcf:Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques. Conversion fractors - mppcf X 35.3 = millon particles per cubic meter = particles per cubic				Short term		
Cement, portland, chemicals   65997-15-1     Eight hours   10 (Total dust)     United States   [4] (Cal/OSHA     United States   [5] (NIOSH)     Eight hours   10 (Total dust)     Short term   5 (Respirable fraction)     Short term   10 (Total dust)     Short term   5 (Respirable fraction)     United States   5 (Respirable fraction)     Short term   110 (Total dust)     Short term   5 (Respirable fraction)     United States   [6] (OSHA)     Eight hours   15 (Total dust)     S (Respirable fraction)   5 (Respirable fraction)     United States   [6] (OSHA)     Eight hours   15 (Total dust)     S (Respirable fraction)   5 (Respirable fraction)     United States   [6] (OSHA)     Eight hours   15 (Total dust)     S (Respirable fraction)   5 (Respirable fraction)     <			Éire [3]	Eight hours		
Cement, portland, chemicals 65997-15-1 United States [4] (Cal/OSHA) Fight hours 5 (Respirable fraction)   Cement, portland, chemicals 65997-15-1 Eight hours 10 (Total dust) 5 (Respirable fraction)   United States [5] (NIOSH) Fight hours 110 (Total dust) 5 (Respirable fraction)   United States [6] (OSHA) Eight hours 115 (Total dust) 5 (Respirable fraction) 50 (mppcf:Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques, Conversion fractors - mppcf X 35.3 = million particles per cubic meter = particles per cubic meter = particles per				Short term		
Short termImage: Constraint of the states is and the states				Eight hours		5 (Respirable
Cement, portland, chemicals   65997-15-1     United States   [5] (NIOSH)     Fight hours   10 (Total dust)     Short term   5 (Respirable fraction)     Short term   15 (Total dust)     United States   [6] (OSHA)     United States   [6] (OSHA)     Eight hours   15 (Total dust)     Short term   15 (Respirable fraction) 50 (mppcf:Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques. Conversion factors - mppcf X 35.3 = million particles per cubic meter = par				Short term		, <u>, , , , , , , , , , , , , , , , , , </u>
Cement, portland, chemicals65997-15-1Short termImage: Comparison of the temperature of temperature						5 (Respirable
United States [6] (OSHA) United States [6] (OSHA) United States [6] (OSHA) Eight hours Samples counted by light-field techniques. Conversion factors - mppcf X 35.3 = million particles per cubic meter = particles per c.c.)				Short term		
Short term	Cement, portland, chemicals	65997-15-1				5 (Respirable fraction) 50 (mppcf:Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques. Conversion factors - mppcf X 35.3 = million particles per cubic meter = particles per
				Short term		,

(in accordance with Regulation (EU) 2020/878)

# FIXCER EUROCOLOR FLEX



Version 1 Date of compilation: 18/02/2020

Version 14 (replaces version 13) Revision date: 17/03/2023

Page 5 of 10 Print date: 24/03/2023

[1] Según la lista de Valores Límite Ambientales de Exposición Profesional adoptados por el Instituto Nacional de Seguridad y Salud en el Trabajo (INSST) para el año 2022.

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive. [3] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

[4] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[5] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health,

Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[6] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs),

California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

The product does NOT contain substances with Biological Limit Values.

### 8.2 Exposure controls.

### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Maintenance:   Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents of adhesives.     Observations:   Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tig Always use with clean, dry hands.     Material:   PVC (polyvinyl chloride)   Breakthrough time (min.):   480   Material thickness (mm):   0,35     Eye protection:   PPE:   Protective goggles against particle impacts.   Material thickness (mm):   0,35     Eye protection:   PPE:   Protective goggles against particle impacts.   CE» marking, category II. Eye protector against dust and smoke.   Opposite the imposite the imposi	entration: 1	ration: 100 %	
PPE:   Particle filter mask     Characteristics:   CE* marking, category III. Made of filtering material, it covers nose, mouth and chin.     CEN standards:   EN 149     Maintenance:   EN 149     Observations:   Subout be replaced after use.     Does not protect worker unless properly adjusted. Follow the manufacturer's instructions regarding suitable use of the equipment.     Filter Type needed:   P2     Hand protection:   PPE:     Characteristics:   «CE* marking, category III.     CEN standards:   EN 374-1, En 374-2, EN 374-3, EN 420     Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as pc adhesives.     Observations:   Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tig adhesives.     Observations:   Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tig adhesives.     Observations:   Always use with clean, dry hands.     Material:   PVC (polyvinyl chloride)   Breakthrough time adminet.     PTE:   Protective goggles against particle impacts.   (mm):     Characteristics:   «CE* marking, category II. Eve protector against dust and smoke.   (E* marking, category II. Forective clousing.     PPE:   Pro			
Characteristics:   «CE» marking, category III. Made of filtering material, it covers nose, mouth and chin.     CEN standards:   EN 149     Maintenance:   Check for any tears, defects, etc. before use. Since it is disposable individual protection equipment should be replaced after use.     Observations:   Does not protect worker unless properly adjusted. Follow the manufacturer's instructions regarding suitable use of the equipment.     Filter Type needed:   P2 <b>Hand protection:</b> Protective gloves against chemicals.     Characteristics:   «CE» marking, category III.     CEN standards:   EN 374-1, En 374-2, EN 374-3, EN 420     Maintenance:   Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.     Observations:   Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tig Always use with clean, dry hands.     Material:   PVC (polyvinyl chloride)   Breakthrough time (min.):   > 480   Material thickness (mm):   0, 35 <b>Eye protection:</b> Protective goggles against particle impacts.   (CE» marking, category II. Eye protector against dust and smoke.   (CE) standards:   EN 165, EN 166, EN 167, EN 168     Maintenance:   Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectore be disinfected periodically following the manufacture			
Characteristics:   chin.     CEN standards:   EN 149     Maintenance:   Check for any tears, defects, etc. before use. Since it is disposable individual protection equipment should be replaced after use.     Observations:   Does not protect worker unless properly adjusted. Follow the manufacturer's instructions regarding suitable use of the equipment.     Filter Type needed:   P2     Hand protection:   PPE:     PFE:   Protective gloves against chemicals.     Characteristics:   CE× marking, category III.     CEN standards:   EN 374-1, En 374-2, EN 374-3, EN 420     Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as pro not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.     Observations:   Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tig dlways use with clean, dry hands.     Material:   PVC (polyvinyl chloride)   Breakthrough time (min.):   > 480   Material thickness (nm):   0,35     Eye protection:   PPE:   Protective goggles against particle impacts.   Characteristics:   CE× marking, category II. Eye protector against dust and smoke.   CEN standards:   EN 165, EN 167, EN 168     Maintenance:   Visibility through lenses should be ideal. Therefore, these parts should be			
Maintenance:   Check for any tears, defects, etc. before use. Since it is disposable individual protection equipment should be replaced after use.     Observations:   Does not protect worker unless properly adjusted. Follow the manufacturer's instructions regarding suitable use of the equipment.     Filter Type needed:   P2     Hand protection:   Protective gloves against chemicals.     Characteristics:   «CE» marking, category III.     CEN standards:   EN 374-1, En 374-2, EN 374-3, EN 420     Maintenance:   Do not make any changes to the gloves that may after their resistance, or apply paints, solvents or adhesives.     Observations:   Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tig Always use with clean, dry hands.     Material:   PVC (polyvinyl chloride)   Breakthrough time (min.):   480   Material thickness (mm):   0,35     Eye protection:   Protective goggles against particle impacts.   Material thickness (mm):   0,35     CEN standards:   EN 165, EN 166, EN 167, EN 168   Imm):   Imm):     Maintenance:   Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors be disinfected periodically following the manufacturer's instructions.   Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenseraping etc.     Skin prot	Teristics'		
Maintenance:   should be replaced after use.     Observations:   Does not protect worker unless properly adjusted. Follow the manufacturer's instructions regarding suitable use of the equipment.     Filter Type needed:   P2     Hand protection:   Protective gloves against chemicals.     Characteristics:   «CE» marking, category III.     CEN standards:   EN 374-1, En 374-2, EN 374-3, EN 420     Maintenance:   Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.     Observations:   Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tig Always use with clean, dry hands.     Material:   PVC (polyvinyl chloride)   Breakthrough time (min.):   > 480   Material thickness (mm):   0,35     Fype protection:   PVC (polyvinyl chloride)   Breakthrough time (min.):   > 480   Material thickness (mm):   0,35     PPE:   Protective goggles against particle impacts.   Characteristics:   «CE» marking, category III. Eve protector against dust and smoke.   Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenser be disinfected periodically following the manufacturer's instructions.     Observations:   Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenser againg etc.			
Observations:   suitable use of the equipment.     Filter Type needed:   P2     Hand protection:   PPE:     Protective gloves against chemicals.   «CE» marking, category III.     CEN standards:   EN 374-1, En 374-2, EN 374-3, EN 420     Maintenance:   Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.     Observations:   Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tig Always use with clean, dry hands.     Material:   PVC (polyvinyl chloride)   Breakthrough time (min.):   480   Material thickness (min.):   0,35     Eye protection:   Protective goggles against particle impacts.   (min.):   0,35   (min.):     PPE:   Protective goggles against particle impacts.   (min.):   0,35     CEN standards:   EN 165, EN 166, EN 167, EN 168   (min.):   (min.):   (min.):     PPE:   Protective clothing.   Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, superficial scratching of the less     Observations:   Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the less     CEN standards:   EN 340   In order to guarantee uniform protective clothing sh	shance: sh	should be replaced after use.	
Hand protection:     PPE:   Protective gloves against chemicals.     Characteristics:   «CE» marking, category III.     CEN standards:   EN 374-1, En 374-2, EN 374-3, EN 420     Maintenance:   Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.     Observations:   Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tig Always use with clean, dry hands.     Material:   PVC (polyvinyl chloride)   Breakthrough time (min.):   480   Material thickness (mm):   0,35     PPE:   Protective goggles against particle impacts.   (mm):   0,35     CEN standards:   EN 165, EN 166, EN 167, EN 168   Image: Solve of the appropriate size and fit he lenses, superficial scratching of the lenses, superficial scratching of the lenses, superficial scratching of the lenses, solvents or adhesive.     CEN standards:   EN 165, EN 167, EN 168   Image: Solvent and tear include: yellow colouring of the lenses, superficial scratching of the lenses, superficial scratching of the lenses, some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses and rear or to obstruct the user's movements.     CEN standards:   EN 340     Maintenance:   Material working, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.	/ations: su	suitable use of the equipment.	
PPE:   Protective gloves against chemicals.     Characteristics:   «CE» marking, category III.     CEN standards:   EN 374-1, En 374-2, EN 374-3, EN 420     Maintenance:   Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.     Observations:   Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tig Always use with clean, dry hands.     Material:   PVC (polyvinyl chloride)   Breakthrough time (min.):   > 480   Material thickness (nm):   0,35 <b>Eye protection:</b> Protective goggles against particle impacts.   Material thickness (nm):   0,35     CEN standards:   EN 165, EN 166, EN 167, EN 168   If the user's instructions.   Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, order not to obstruct the user's movements.     CEN standards:   EN 340   In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided to terms of the hazard against which it	1		
Characteristics:   «CE» marking, category III.     CEN standards:   EN 374-1, En 374-2, EN 374-3, EN 420     Maintenance:   Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.     Observations:   Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tig Always use with clean, dry hands.     Material:   PVC (polyvinyl chloride)   Breakthrough time (min.):   > 480   Material thickness (n,35) <b>Eye protection:</b> Protective goggles against particle impacts.     0,35     CEN standards:   EN 165, EN 166, EN 167, EN 168   Image: Source of the appropriate size and fit the user's instructions.   Source of the appropriate size and fit the user's instructions.     Maintenance:   Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors be disinfected periodically following the manufacturer's instructions.   Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses scraping etc.     Skin protection:   PPE:   Protective clothing.      PPE:   Protective clothing.   CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.      CEN standards:   EN 340   In order to guarantee uniform protection, follow the washing			
Maintenance:   Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as por adhesives.     Observations:   Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tig Always use with clean, dry hands.     Material:   PVC (polyvinyl chloride)   Breakthrough time (min.):   > 480   Material thickness (mm):   0,35     Eye protection:   PVC (polyvinyl chloride)   Breakthrough time (min.):   > 480   Material thickness (mm):   0,35     Eye protection:   PVC (polyvinyl chloride)   Breakthrough time (min.):   > 480   Material thickness (mm):   0,35     Eye protection:   Protective goggles against particle impacts.   CEN standards:   EN 165, EN 166, EN 167, EN 168   Image: Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lense some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lense scraping etc.     Skin protection:   PPE:   Protective clothing.   CEN marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.   EN 340     CEN standards:   EN 340   In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer.   The protective clothing should offer a level of comfort in line with the level of protection provided the manufacturer. <			
Maintenance:   Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents of adhesives.     Observations:   Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tig Always use with clean, dry hands.     Material:   PVC (polyvinyl chloride)   Breakthrough time (min.):   > 480   Material thickness (mm):   0,35     Eye protection:   PVC (polyvinyl chloride)   Breakthrough time (min.):   > 480   Material thickness (mm):   0,35     Eye protection:   PVE:   Protective goggles against particle impacts.   (mm):   0,35     CEN standards:   EN 165, EN 166, EN 167, EN 168   Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses scraping etc.     Skin protection:   Protective clothing.   «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.     CEN standards:   EN 340   In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided the manufacturer. The protective clothing	andards: El	Jards: EN 374-1, En 374-2, EN 374-3, EN 420	
Observations:   Always use with clean, dry hands.   Material:   PVC (polyvinyl chloride)   Breakthrough time (min.):   Always use with clean, dry hands.     Material:   PVC (polyvinyl chloride)   Breakthrough time (min.):   > 480   Material thickness (mm):   0,35     Eye protection:   PPE:   Protective goggles against particle impacts.   (mm):   0,35     Characteristics:   «CE» marking, category II. Eye protector against dust and smoke.   (mm):   (mm):   (mm):     CEN standards:   EN 165, EN 166, EN 167, EN 168   (min.):   (min.):   (min.):   (min.):     Maintenance:   Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors be disinfected periodically following the manufacturer's instructions.   Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the less scraping etc.     Skin protection:   PPE:   Protective clothing.   (CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.     CEN standards:   EN 340   In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer.     Maintenance:   In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer.     The prot			
Material:   PVC (polyViny chorde)   (min.):   > 480   (mm):   0,35     Eye protection:   PPE:   Protective goggles against particle impacts.   (mm):   0,35     Characteristics:   «CE» marking, category II. Eye protector against dust and smoke.   (mm):   0,35     CEN standards:   EN 165, EN 166, EN 167, EN 168   (mm):   0,35     Maintenance:   Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors be disinfected periodically following the manufacturer's instructions.   Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses scraping etc.     Skin protection:   PPE:   Protective clothing.     CEN standards:   EN 340     Maintenance:   In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer.     Maintenance:   In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer.     Observations:   EN 340     Maintenance:   In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer.     Observations:   The protective clothing should offer a level of comfort in line with the level of protection provided it terms of the hazard against which it protects, bearing in mind environmental conditi		Always use with clean, dry hands.	
PPE:   Protective goggles against particle impacts.     Characteristics:   «CE» marking, category II. Eye protector against dust and smoke.     CEN standards:   EN 165, EN 166, EN 167, EN 168     Maintenance:   Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors be disinfected periodically following the manufacturer's instructions.     Observations:   Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses craping etc.     Skin protection:   PPE:     PPE:   Protective clothing.     Characteristics:   «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.     CEN standards:   EN 340     Maintenance:   In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided to terms of the hazard against which it protects, bearing in mind environmental conditions, the user's	al: PVC		
Characteristics:«CE» marking, category II. Eye protector against dust and smoke.CEN standards:EN 165, EN 166, EN 167, EN 168Maintenance:Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors be disinfected periodically following the manufacturer's instructions. Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the le scraping etc.Skin protection:Protective clothing. «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.CEN standards:EN 340Maintenance:In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided terms of the hazard against which it protects, bearing in mind environmental conditions, the user's	rotection:	ection:	
CEN standards:   EN 165, EN 166, EN 167, EN 168     Maintenance:   Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors be disinfected periodically following the manufacturer's instructions.     Observations:   Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, superficial scratching of the lenses.     Skin protection:   PPE:     PPE:   Protective clothing.     Characteristics:   «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.     CEN standards:   EN 340     Maintenance:   In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided to the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided to the manufacturer.			
Maintenance:   Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors be disinfected periodically following the manufacturer's instructions.     Observations:   Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses scraping etc.     Skin protection:   Protective clothing.     Characteristics:   «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.     CEN standards:   EN 340     Maintenance:   In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer.     Observations:   The protective clothing should offer a level of comfort in line with the level of protection provided to the scraping should offer a level of comfort in line with the level of protection provided to the scraping should offer a level of comfort in line with the level of protection provided to the scraping in mind environmental conditions, the user's movements	teristics: «	istics: «CE» marking, category II. Eye protector against dust and smoke.	
Maintenance:   be disinfected periodically following the manufacturer's instructions.     Observations:   Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses     Skin protection:   PPE:     PPE:   Protective clothing.     Characteristics:   «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.     CEN standards:   EN 340     Maintenance:   In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided terms of the hazard against which it protects, bearing in mind environmental conditions, the user's	andards: El	Jards: EN 165, EN 166, EN 167, EN 168	
Observations:   scraping etc.     Skin protection:   PPE:     PPE:   Protective clothing.     Characteristics:   «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.     CEN standards:   EN 340     Maintenance:   In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided terms of the hazard against which it protects, bearing in mind environmental conditions, the user's	benance: be	be disinfected periodically following the manufacturer's instructions.	
PPE:   Protective clothing.     Characteristics:   «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.     CEN standards:   EN 340     Maintenance:   In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer.     Observations:   The protective clothing should offer a level of comfort in line with the level of protection provided to the mazer against which it protects, bearing in mind environmental conditions, the user's			
Characteristics:«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.CEN standards:EN 340Maintenance:In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided terms of the hazard against which it protects, bearing in mind environmental conditions, the user's			
CHARACTERISTICS.   order not to obstruct the user's movements.     CEN standards:   EN 340     Maintenance:   In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer.     Observations:   The protective clothing should offer a level of comfort in line with the level of protection provided terms of the hazard against which it protects, bearing in mind environmental conditions, the user's			
Maintenance:In order to guarantee uniform protection, follow the washing and maintenance instructions provide the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided terms of the hazard against which it protects, bearing in mind environmental conditions, the user's	or	order not to obstruct the user's movements.	
Maintenance:   the manufacturer.     The protective clothing should offer a level of comfort in line with the level of protection provided     Observations:   terms of the hazard against which it protects, bearing in mind environmental conditions, the user's			
Observations: terms of the hazard against which it protects, bearing in mind environmental conditions, the user's	th	the manufacturer.	
	vations: te	ons: terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level	
PPE: Work footwear.			
Characteristics: «CE» marking, category II.			
CEN standards: EN ISO 13287, EN 20347 Maintenance: This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should be used by other people.	TI	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should	

(in accordance with Regulation (EU) 2020/878)

# FIXCER EUROCOLOR FLEX



Date of compilation: 18/02/2020 Version 1

Version 14 (replaces version 13) Revision date: 17/03/2023

Page 6 of 10 Print date: 24/03/2023

Work footwear for professional use includes protection elements aimed at protecting users against any Observations: injury resulting from an accident

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties. Physical state: Solid - Dust Colour: Not applicable/Not available due to the nature/properties of the product Odour: Not applicable/Not available due to the nature/properties of the product Odour threshold: Not applicable/Not available due to the nature/properties of the product Melting point: Not applicable/Not available due to the nature/properties of the product Freezing point: Not applicable/Not available due to the nature/properties of the product Boiling point or initial boiling point and boiling range: Not applicable/Not available due to the nature/properties of the product Flammability: Not applicable/Not available due to the nature/properties of the product Lower explosion limit: Not applicable/Not available due to the nature/properties of the product Upper explosion limit: Not applicable/Not available due to the nature/properties of the product Flash point: > 60 °C Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product Decomposition temperature: Not applicable/Not available due to the nature/properties of the product pH: Not applicable/Not available due to the nature/properties of the product Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product Solubility: Not applicable/Not available due to the nature/properties of the product Hydrosolubility: Not applicable/Not available due to the nature/properties of the product Liposolubility: Not applicable/Not available due to the nature/properties of the product Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product Vapour pressure: Not applicable/Not available due to the nature/properties of the product Absolute density: Not applicable/Not available due to the nature/properties of the product Relative density: Not applicable/Not available due to the nature/properties of the product Relative vapour density: Not applicable/Not available due to the nature/properties of the product Particle characteristics: Not applicable/Not available due to the nature/properties of the product

#### 9.2 Other information

Not applicable/Not available due to the nature/properties of the product

### SECTION 10: STABILITY AND REACTIVITY.

#### 10.1 Reactivity.

The product does not present hazards by their reactivity.

#### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

#### 10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

#### 10.4 Conditions to avoid.

Avoid any improper handling.

#### 10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

#### 10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

### SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

(in accordance with Regulation (EU) 2020/878)

# FIXCER EUROCOLOR FLEX



Version 1 Date of compilation: 18/02/2020

Version 14 (replaces version 13) Revision date: 17/03/2023

Page 7 of 10 Print date: 24/03/2023

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

### 11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity; Not conclusive data for classification.

b) skin corrosion/irritation;Product classified:Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation; Product classified: Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation; Product classified: Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Not conclusive data for classification.

h) STOT-single exposure;
Product classified:
Specific target organ toxicity following a single exposure, Category 3: May cause respiratory irritation.

i) STOT-repeated exposure; Not conclusive data for classification.

j) aspiration hazard; Not conclusive data for classification.

#### 11.2 Information on other hazards.

### Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health. **Other information** 

There is no information available on other adverse health effects.

### SECTION 12: ECOLOGICAL INFORMATION.

#### 12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

#### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present. No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

#### 12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

(in accordance with Regulation (EU) 2020/878)

# FIXCER EUROCOLOR FLEX



Version 1 Date of compilation: 18/02/2020

Version 14 (replaces version 13) Revision date: 17/03/2023

Page 8 of 10 Print date: 24/03/2023

#### 12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

#### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

#### 12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

#### 12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

### SECTION 13: DISPOSAL CONSIDERATIONS.

#### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

### SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

#### 14.1 UN number or ID number.

Transportation is not dangerous.

#### 14.2 UN proper shipping name.

Description: ADR/RID: Not classified as hazardous for transport. IMDG: Not classified as hazardous for transport. ICAO/IATA: Not classified as hazardous for transport.

#### 14.3 Transport hazard class(es).

Transportation is not dangerous.

#### 14.4 Packing group.

Transportation is not dangerous.

#### 14.5 Environmental hazards.

Transportation is not dangerous. Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): Not applicable.

#### 14.6 Special precautions for user.

Transportation is not dangerous.

#### 14.7 Maritime transport in bulk according to IMO instruments.

Transportation is not dangerous.

### **SECTION 15: REGULATORY INFORMATION.**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC) VOC content (p/p): 0 % VOC content: 0 g/l

(in accordance with Regulation (EU) 2020/878)

### FIXCER EUROCOLOR FLEX



Version 1 Date of compilation: 18/02/2020

Version 14 (replaces version 13) Revision date: 17/03/2023

Page 9 of 10 Print date: 24/03/2023

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

#### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### **SECTION 16: OTHER INFORMATION.**

Complete text of the H phrases that appear in section 3:

H317	May cause an allergic	skin reaction.

- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.

Classification codes:

Eye Dam. 1 : Serious eye damage, Category 1 STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3 Skin Irrit. 2 : Skin irritant, Category 2 Skin Sens. 1 : Skin sensitiser, Category 1 Skin Sens. 1B : Skin sensitiser, Category 1B

Changes regarding to the previous version:

- Change of the name of the product (SECTION 1.1).
- Change of the uses of the product (SECTION 1.2).
- Change in the emergency number (SECTION 1.4).
- Modification of specific hazards (SECTION 2.3).
- Changes in the composition of the product (SÉCTION 3.2).
- Modification in the firefighting measures (SECTION 5.2).
- Modifications in the accidental release measures (SECTION 6.1).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Change in the hazard classification (SECTION 11.1).
- Modification of the classification ADR/IMDG/ICAO/IATA/RID (SECTION 14).

# Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

CEN: European Committee for Standardization.

PPE: Personal protection equipment.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2020/878.

(in accordance with Regulation (EU) 2020/878)

# FIXCER EUROCOLOR FLEX



Version 1Date of compilation: 18/02/2020Version 14 (replaces version 13)Revision date: 17/03/2023

Page 10 of 10 Print date: 24/03/2023

Regulation (EC) No 1907/2006. Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.