



TECHNICAL SPECIFICATIONS

Nº 031/13

Manufacturer:

Fixcer Products, S.A. - Ctra. Sant Cugat, Km 3 - 08290 Cerdanyola del Vallès (Barcelona)
Telf. 93 580 20 00 ; Fax 93 580 15 51
Planta: Avda. Gaudí, 15 – Pol. Ind. Rubí Sur – 08191 Rubí (Barcelona)

Identification code:

Name:	EUROCOLOR FLEX
Product type:	CG2 WA

Intended use:

Grouting material for joints from 0 to 16 mm between ceramic tiles, on walls and floors, both indoors and outdoors

Declared technical characteristics:

Technical specifications	Values	Standard
High resistance to abrasion	$\leq 1000 \text{ mm}^3$	UNE EN 13888:2009
Flexural strength after dry storage	$\geq 2.5 \text{ N/mm}^2$	
Flexural strength after freeze-thaw cycles	$\geq 2.5 \text{ N/mm}^2$	
Compressive strength after dry storage	$\geq 15 \text{ N/mm}^2$	
Compressive strength after freeze-thaw cycles	$\geq 15 \text{ N/mm}^2$	
Retraction	$\leq 3 \text{ mm/m}$	
Reduced water absorption after 30 min.	$\leq 2 \text{ g}$	
Reduced water absorption after 240 min.	$\leq 5 \text{ g}$	
Fire reaction	A1	

Signed by and on behalf of the manufacturer by:

Inés Sánchez
Directora Técnica

Cerdanyola del Vallès: 06-04-2021

