



DECLARATION OF PERFORMANCE

Nº 136.01/18

Manufacturer:

Fixcer Products, S.A. - Ctra. Sant Cugat, Km 3 - 08290 Cerdanyola del Vallès (Barcelona)
Telf. 93 580 20 00 ; Fax 93 580 15 51
Planta: Avda. Gaudí, 15 – Pol. Ind. Rubí Sur – 08191 Rubí (Barcelona)

Identification code:

Name:	TRIPLE F GEL
Product type:	CMP

Intended use:

Cementitious polymer-modified waterproofing membrane used under ceramic tiles.

System of evaluation and verification of the constancy of performance:

	4
Sealing	3

Harmonised standard:

EN 14891:2017

Notified body:

LGA Technological Center, nº 0370

Declared performance:

Essential characteristics:	Performance	Technical specifications
Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2017
Sealing	No penetration	
Crack propagation resistance under normal conditions	$\geq 0,75 \text{ mm}$	
Durability of the initial tensile adhesion against thermal ageing / weathering	$\geq 0,5 \text{ N/mm}^2$	
Durability of the initial tensile adhesion against the action of water / moisture	$\geq 0,5 \text{ N/mm}^2$	
Durability of initial tensile adhesion against freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$	
Durability of initial tensile adhesion against immersion in lime water	$\geq 0,5 \text{ N/mm}^2$	
Durability of initial tensile adhesion against chlorinated water action	$\geq 0,5 \text{ N/mm}^2$	
Discharge of hazardous substances	View SDS	

The performance of the previously identified product is in accordance with the declared performance.

This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer indicated above.

Signed by and on behalf of the manufacturer by:

Inés Sánchez
Directora Técnica

Cerdanyola del Vallès: 18-03-22





DECLARATION OF PERFORMANCE

Nº 136.02/18

Manufacturer:

Fixcer Products, S.A. - Ctra. Sant Cugat, Km 3 - 08290 Cerdanyola del Vallès (Barcelona)

Telf. 93 580 20 00 ; Fax 93 580 15 51

Planta: Avda. Gaudí, 15 – Pol. Ind. Rubí Sur – 08191 Rubí (Barcelona)

Identification code:

Name:	TRIPLE F GEL
Product type:	C2TES1

Intended use:

All indoor and outdoor installation

System of evaluation and verification of the constancy of performance:

3

Harmonised standard:

EN 12004-1:2017

Notified body:

LGAI Technological Center, nº 0370

Declared performance:

Essential characteristics:	Performance	Technical specifications
Fire reaction	A1	EN 12004-1:2017
Discharge of hazardous substances	View SDS	
Initial adhesion	$\geq 1,0 \text{ N/mm}^2$	
Adhesion after thermal ageing	$\geq 1,0 \text{ N/mm}^2$	
Adhesion after immersion in water	$\geq 1,0 \text{ N/mm}^2$	
Adhesion after freeze-thaw cycles	$\geq 1,0 \text{ N/mm}^2$	

The performance of the previously identified product is in accordance with the declared performance.

This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer indicated above.

Signed by and on behalf of the manufacturer by:

Inés Sánchez
Directora Técnica

Cerdanyola del Vallès: 18-03-2022





DECLARATION OF PERFORMANCE

Nº 136.03/18

Manufacturer:

Fixcer Products, S.A. - Ctra. Sant Cugat, Km 3 - 08290 Cerdanyola del Vallès (Barcelona)
Telf. 93 580 20 00 ; Fax 93 580 15 51
Planta: Avda. Gaudí, 15 – Pol. Ind. Rubí Sur – 08191 Rubí (Barcelona)

Identification code:

Name:	TRIPLE F GEL
Product type:	C, MC - RI

Intended use:

Coating for surface protection of concrete

System of evaluation and verification of the constancy of performance:

4

Harmonised standard:

EN 1504-2:2004

Notified body:

LGAi Technological Center, nº 0370

Declared performance:

Essential characteristics:	Performance	Technical specifications
Water vapour permeability	Class I: sd <5 m	EN 1504-2:2004
Capillary absorption and water permeability	$w < 0,1 \text{ kg/m}^2 \cdot \text{h}^{0,5}$	
Adhesion by pull-off test	Flexible system: No traffic load $\geq 0,8 \text{ N/mm}^2$ With traffic load $\geq 1,5 \text{ N/mm}^2$	
Fire reaction	E	
Hazardous substances	View SDS	

The performance of the previously identified product is in accordance with the declared performance.

This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer indicated above.

Signed by and on behalf of the manufacturer by:

Inés Sánchez
Directora Técnica

Cerdanyola del Vallès: 18-03-2022



TECHNICAL SPECIFICATIONS

Nº 136.04/18

Manufacturer:

Fixcer Products, S.A. - Ctra. Sant Cugat, Km 3 - 08290 Cerdanyola del Vallès (Barcelona)

Telf. 93 580 20 00 ; Fax 93 580 15 51

Planta: Avda. Gaudí, 15 – Pol. Ind. Rubí Sur – 08191 Rubí (Barcelona)

Identification code:

Name:	TRIPLE F GEL
Product type:	CG2 WA

Intended use:

Grouting material for joints from 0 to 16 mm between ceramic tiles, on walls and floors, both indoors and outdoors

Declared technical characteristics:

Technical specifications	Values	Standard
High resistance to abrasion	$\leq 1000 \text{ mm}^3$	UNE EN 13888:2009
Flexural strength after dry storage	$\geq 2.5 \text{ N/mm}^2$	
Flexural strength after freeze-thaw cycles	$\geq 2.5 \text{ N/mm}^2$	
Compressive strength after dry storage	$\geq 15 \text{ N/mm}^2$	
Compressive strength after freeze-thaw cycles	$\geq 15 \text{ N/mm}^2$	
Retraction	$\leq 3 \text{ mm/m}$	
Reduced water absorption after 30 min.	$\leq 2 \text{ g}$	
Reduced water absorption after 240 min.	$\leq 5 \text{ g}$	
Fire reaction	A1	

Signed by and on behalf of the manufacturer by:



Inés Sánchez
Directora Técnica

Cerdanyola del Vallès: 18-03-2022

