

## DECLARATION OF PERFORMANCE

Nº 036.01/13

**Manufacturer:**

Fixcer Products, S.A. - Ctra. Sant Cugat, Km 3 - 08290 Cerdanyola del Vallès (Barcelona)  
Telf. 93 580 20 00 ; Fax 93 580 15 51  
Planta: Avda. Gaudí, 15 – Pol. Ind. Rubí Sur – 08191 Rubí (Barcelona)

**Identification code:**

|                      |                        |
|----------------------|------------------------|
| <b>Name:</b>         | <b>PROFESSIONAL PX</b> |
| <b>Product type:</b> | <b>R2T</b>             |

**Intended use:**

All indoor and outdoor installation

**System of evaluation and verification of the constancy of performance:**

**3**

**Harmonised standard:**

**EN 12004:2007+A1:2012**

**Notified body:**

**LGAI Technological Center, nº 0370**

**Declared performance:**

| <b>Essential characteristics:</b>       | <b>Performance</b>      | <b>Technical specifications</b> |
|---|-------------------------|---------------------------------|
| Fire reaction                           | E                       | EN 12004:2007+A1:2012           |
| Discharge of hazardous substances       | View SDS                |                                 |
| Initial shear adhesion                  | ≥ 2,0 N/mm <sup>2</sup> |                                 |
| Shear adhesion after thermal shock      | ≥ 2,0 N/mm <sup>2</sup> |                                 |
| Shear adhesion after immersion in water | ≥ 2,0 N/mm <sup>2</sup> |                                 |

The performance of the previously identified product is in accordance with the declared performance.

This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer indicated above.

**Signed by and on behalf of the manufacturer by:**



*Inés Sánchez*  
Directora Técnica

Cerdanyola del Vallès: 06-04-2021



## TECHNICAL SPECIFICATIONS

Nº 036.02/13

### Manufacturer:

Fixcer Products, S.A. - Ctra. Sant Cugat, Km 3 - 08290 Cerdanyola del Vallès (Barcelona)

Telf. 93 580 20 00 ; Fax 93 580 15 51

Planta: Avda. Gaudí, 15 – Pol. Ind. Rubí Sur – 08191 Rubí (Barcelona)

### Identification code:

|                      |                        |
|----------------------|------------------------|
| <b>Name:</b>         | <b>PROFESSIONAL PX</b> |
| <b>Product type:</b> | <b>RG</b>              |

### Intended use:

Anti-acid grouting material between ceramic tiles, on walls and floors, both indoors and outdoors

### Declared technical characteristics:

| Technical specifications                | Values                   | Standard          |
|---|--------------------------|-------------------|
| High resistance to abrasion             | $\leq 250 \text{ mm}^3$  | UNE EN 13888:2009 |
| Flexural strength after dry storage     | $\geq 30 \text{ N/mm}^2$ |                   |
| Compressive strength after dry storage  | $\geq 45 \text{ N/mm}^2$ |                   |
| Retraction                              | $\leq 1,5 \text{ mm/m}$  |                   |
| Reduced water absorption after 240 min. | $\leq 0,1 \text{ g}$     |                   |
| Fire reaction                           | E                        |                   |

### Signed by and on behalf of the manufacturer by:



*Inés Sánchez*  
Directora Técnica

Cerdanyola del Vallès: 06-04-2021

