



DECLARATION OF PERFORMANCE

Nº 065/13

Manufacturer:

Fixcer Products, S.A. - Ctra. Sant Cugat, Km 3 - 08290 Cerdanyola del Vallès (Barcelona)
Telf. 93 580 20 00 ; Fax 93 580 15 51
Planta: Avda. Gaudí, 15 – Pol. Ind. Rubí Sur – 08191 Rubí (Barcelona)

Identification code:

Name:	SILICONA NEUTRA
Product type:	Transparent: F-EXT-INT-CC; EN 15651-1:2012 G-CC; EN 15651-2:2012 S; EN 15651-3:2012 RG
Product type:	Colours: F-EXT-INT-CC; EN 15651-1:2012 G-CC; EN 15651-2:2012

Intended use:

Transparent: Sealant for façade elements, interior and exterior application; sealant for glazing and sealant for sanitary seals
Colours: sealant for façade elements, interior and exterior application; glazing sealant

System of evaluation and verification of the constancy of performance:

3

Harmonised standard:

Transparent:	EN 15651-1:2012, EN 15651-2:2012, EN 15651-3:2012
Colours:	EN 15651-1:2012, EN 15651-2:2012

Notified body:

SKZ-TeConA GmbH, nº NB01213

Declared performance:

Transparent sealant:

Essential characteristics:	Performance	Technical specifications
Fire reaction	E	EN 15651-1:2012 EN 15651-2:2012 EN 15651-3:2012
Release of hazardous chemicals into the environment	NPD	
Air and water tightness:		
Volume loss	≤ 10%	
Resistance to flaking	≤ 2 mm	
Tensile properties at maintained extension after immersion in water	SF	
Tensile properties at maintained extension for non-structural sealants used in joints in cold climatic zones (-30°C)	SF	
Artificial light exposure adhesion/cohesion properties (preconditioning method B)	SF	
Elastic recovery	≥ 70%	
Evaluation of the action of micro-organisms	1	
Durability	Pass	

Packaging: Method A; Substrate: Aluminium and glass without primer; M1 mortar with primer

Colour sealant:

Essential characteristics:	Performance	Technical specifications
Fire reaction	E	EN 15651-1:2012 EN 15651-2:2012
Release of hazardous chemicals into the environment	NPD	
Air and water tightness:		
Volume loss	≤ 10%	
Resistance to flaking	≤ 3 mm	
Tensile properties at maintained extension after immersion in water	SF	
Tensile properties at maintained extension for non-structural sealants used in joints in cold climatic zones (-30°C)	SF	
Adhesion/cohesion properties on exposure to heat, water, and artificial light	SF	
Elastic recovery	≥ 70%	
Durability	Pass	

Packaging: Method B; Substrate: Aluminium, glass and M2 mortar without primer; M1 mortar with primer

The performance of the previously identified product is in accordance with the declared performance.

This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer indicated above.

Signed by and on behalf of the manufacturer by:

Inés Sánchez
Directora Técnica

Cerdanyola del Vallès: 06-04-2021

